

(12) **United States Patent**
Fischer et al.

(10) **Patent No.:** **US 9,178,636 B2**
(45) **Date of Patent:** **Nov. 3, 2015**

(54) **UNIVERSAL REMOTE RADIO HEAD**

USPC 370/254–350; 709/201–213
See application file for complete search history.

(71) Applicant: **ADC Telecommunications, Inc.**,
Shakopee, MN (US)

(56) **References Cited**

(72) Inventors: **Larry G. Fischer**, Waseca, MN (US);
Philip M. Wala, Savage, MN (US);
Dean Zavadsky, Shakopee, MN (US);
Lance K. Uyehara, San Jose, CA (US);
Jody Forland, St. Bonifacius, MN (US)

U.S. PATENT DOCUMENTS

4,183,054 A 1/1980 Patisaul et al.
4,451,916 A 5/1984 Casper et al.

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **ADC Telecommunications, Inc.**,
Berwyn, PA (US)

CA 2058736 7/1993
CA 2058737 7/1993

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

European Patent Office, “Extended European Search Report from EP
Application No. 11813094.7 mailed Aug. 14, 2013”, “from Foreign
Counterpart of U.S. Appl. No. 12/845,060”, Aug. 14, 2013, pp. 16,
Published in: EP.

(21) Appl. No.: **14/187,135**

(22) Filed: **Feb. 21, 2014**

(Continued)

(65) **Prior Publication Data**

US 2014/0241224 A1 Aug. 28, 2014

Primary Examiner — Ayaz Sheikh

Assistant Examiner — Debebe Asefa

(74) *Attorney, Agent, or Firm* — Fogg & Powers LLC

Related U.S. Application Data

(60) Provisional application No. 61/768,038, filed on Feb.
22, 2013.

(51) **Int. Cl.**
H04J 3/00 (2006.01)
H04W 88/08 (2009.01)
(Continued)


(52) **U.S. Cl.**
CPC **H04J 3/00** (2013.01); **H04H 20/79** (2013.01);
H04N 21/2385 (2013.01); **H04W 88/085**
(2013.01)

(58) **Field of Classification Search**
CPC . H04L 41/5022; H04L 47/2408; H04L 47/32;
H04L 41/509; H04L 47/30; H04L 47/14;
H04L 47/20; H04L 47/2416; H04L 47/2425;
H04L 47/2441; H04N 21/64792; H04N
21/234327; H04N 21/2381; H04N 21/8451

(57) **ABSTRACT**

A distributed base station radio system includes first channel-
ized to broadband conversion unit that receives first downlink
channelized data for first radio frequency band from first
channelized radio frequency source; and first universal
remote radio head communicatively coupled to first channel-
ized to broadband conversion unit. First channelized to broad-
band conversion unit converts first downlink channelized data
into a first downlink broadband signal. First channelized to
broadband conversion unit communicates the first downlink
broadband signal to first universal remote radio head. First
universal remote radio head receives first downlink broad-
band signal. First universal remote radio head frequency con-
verts the first downlink broadband signal into first downlink
radio frequency signals in first radio frequency band. First
universal remote radio head is further configured to transmit
first downlink radio frequency signals in first radio frequency
band to first subscriber unit.

43 Claims, 19 Drawing Sheets



(51)	Int. Cl.		6,917,614 B1	7/2005	Laubach et al.
	H04H 20/79	(2008.01)	6,963,552 B2	11/2005	Sabat, Jr. et al.
	H04N 21/2385	(2011.01)	7,127,175 B2	10/2006	Mani et al.
			7,205,864 B2	4/2007	Schultz, Jr. et al.
			7,215,651 B2	5/2007	Millar
(56)	References Cited		7,289,972 B2	10/2007	Rieser et al.
	U.S. PATENT DOCUMENTS		7,313,415 B2	12/2007	Wake et al.
			7,489,641 B2 *	2/2009	Miller et al. 370/241.1
			7,733,901 B2	6/2010	Salkini et al.
			7,761,093 B2	7/2010	Sabat, Jr. et al.
			7,787,854 B2	8/2010	Conyers et al.
			7,920,858 B2	4/2011	Sabat, Jr. et al.
			8,902,769 B1 *	12/2014	Dehghan et al. 370/252
			8,964,641 B2 *	2/2015	Dalela et al. 370/328
			2001/0036163 A1	11/2001	Sabat, Jr. et al.
			2001/0044292 A1	11/2001	Jeon et al.
			2002/0142739 A1	10/2002	Smith
			2002/0167954 A1	11/2002	Highsmith et al.
			2002/0191565 A1	12/2002	Mani et al.
			2003/0015943 A1	1/2003	Kim et al.
			2003/0043928 A1	3/2003	Ling et al.
			2003/0203717 A1	10/2003	Chuprun et al.
			2004/0010609 A1	1/2004	Vilander et al.
			2004/0032354 A1	2/2004	Knobel et al.
			2004/0037565 A1	2/2004	Young et al.
			2004/0053602 A1	3/2004	Wurzburg
			2004/0106387 A1	6/2004	Bauman et al.
			2004/0106435 A1	6/2004	Bauman et al.
			2004/0132474 A1	7/2004	Wala
			2004/0198453 A1	10/2004	Cutrer et al.
			2004/0203339 A1	10/2004	Bauman
			2004/0203703 A1	10/2004	Fischer
			2004/0219950 A1	11/2004	Pallonen et al.
			2005/0147067 A1	7/2005	Mani et al.
			2005/0201323 A1	9/2005	Mani et al.
			2005/0250503 A1	11/2005	Cutrer
			2006/0026017 A1	2/2006	Walker
			2006/0066484 A1	3/2006	Sayers
			2006/0094470 A1	5/2006	Wake et al.
			2006/0121944 A1	6/2006	Buscaglia et al.
			2006/0153070 A1	7/2006	DelRegno et al.
			2006/0172775 A1	8/2006	Conyers et al.
			2006/0193295 A1	8/2006	White et al.
			2007/0008939 A1	1/2007	Fischer
			2009/0316608 A1	12/2009	Singh et al.
			2009/0316611 A1	12/2009	Stratford et al.
			2010/0177759 A1	7/2010	Fischer et al.
			2010/0215028 A1	8/2010	Fischer
			2011/0143649 A1	6/2011	Sabat, Jr. et al.
			2012/0027145 A1	2/2012	Uyehara et al.
			2012/0106963 A1	5/2012	Huang et al.
			2012/0300766 A1	11/2012	Chen et al.
			2013/0272463 A1	10/2013	Uyehara et al.
			2013/0329633 A1 *	12/2013	Dalela et al. 370/328
					FOREIGN PATENT DOCUMENTS
			CA	2069462	7/1993
			CA	2087285	1/1994
			CA	2138763	1/1994
			CA	2156046	1/1995
			CA	2125411	5/1995
			CA	2128842	1/1996
			CA	2134365	4/1996
			CA	2158386	3/1997
			CA	2168681	8/1997
			CA	2215079	3/1999
			EP	0391597	10/1990
			EP	0876073	11/1998
			EP	1214809	3/2006
			GB	2253770	9/1992
			GB	2289198	11/1995
			GB	2315959	2/1998
			GB	2320653	6/1998
			JP	2000333240	11/2000
			JP	2001197012	7/2001
			JP	2003023396	1/2003
			JP	2004180220	6/2004
			JP	2004194351	7/2004

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	9115927	10/1991
WO	9413067	6/1994
WO	9533350	12/1995
WO	9628946	9/1996
WO	9716000	5/1997
WO	9732442	9/1997
WO	9824256	6/1998
WO	9937035	7/1999
WO	0117156	3/2001
WO	0174013	10/2001
WO	0174100	10/2001
WO	0182642	11/2001
WO	03079645	9/2003
WO	2004054290	6/2004
WO	2009138876	11/2009
WO	2009155602	12/2009

OTHER PUBLICATIONS

U.S. Patent and Trademark Office, "Notice of Allowance", "U.S. Appl. No. 12/845,060", Mar. 4, 2013, pp. 1-10.

U.S. Patent and Trademark Office, "Corrected Notice of Allowability and Interview Summary", "U.S. Appl. No. 12/845,060", Mar. 28, 2013, pp. 1-25.

U.S. Patent and Trademark Office, "Office Action", "U.S. Appl. No. 12/845,060", Oct. 2, 2012, pp. 1-28.

U.S. Patent and Trademark Office, "Office Action", "from U.S. Appl. No. 13/914,838", Nov. 20, 2013, pp. 1-47, Published in: US.

International Preliminary Examining Authority, "International Preliminary Report on Patentability from PCT Application No. PCT/US2011/045495 mailed Feb. 7, 2013", "from Foreign Counterpart of U.S. Appl. No. 12/845,060", Feb. 7, 2013, pp. 1-6, Published in: WO.

International Searching Authority, "International Search Report and Written Opinion from PCT Application No. PCT/US2011/045495 mailed Feb. 17, 2012", "from Foreign Counterpart of U.S. Appl. No. 12/845,060", Feb. 17, 2012, pp. 1-9, Published in: WO.

International Preliminary Examining Authority, "International Preliminary Report on Patentability from PCT Application No. PCT/US2011/057575 mailed May 10, 2013", "from Foreign Counterpart of U.S. Appl. No. 12/913,179", May 10, 2013, pp. 1-7, Published in: WO.

U.S. Patent and Trademark Office, "Office Action", "U.S. Appl. No. 12/913,179", Mar. 18, 2013, pp. 1-49.

International Searching Authority, "International Search Report and Written Opinion from PCT Application No. PCT/US2011/057575 mailed Feb. 17, 2012", "from Foreign Counterpart of U.S. Appl. No. 12/913,179", Feb. 17, 2012, pp. 1-10, Published in: WO.

Chinese Patent Office, "Notification to Grant Patent Right for Invention from CN Application No. 200680029629.2 mailed Mar. 2, 2012", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Mar. 2, 2012, pp. 1-4, Published in: CN.

Chinese Patent Office, "First Office Action from CN Application No. 200680029629.2 mailed Oct. 9, 2010", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Oct. 9, 2010, pp. 1-33, Published in: CN.

Chinese Patent Office, "Second Office Action from CN Application No. 200680029629.2 mailed Aug. 10, 2011", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Aug. 10, 2011, pp. 1-31, Published in: CN.

Chinese Patent Office, "Third Office Action from CN Application No. 200680029629.2 mailed Nov. 16, 2011", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Nov. 16, 2011, pp. 1-10, Published in: CN.

European Patent Office, "Communication under Rule 71(3) EPC from EP Application No. 06772594.5 mailed Sep. 13, 2012", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Sep. 13, 2012, pp. 1-40.

European Patent Office, "Office Action from EP Application No. 06772594.5 mailed Apr. 14, 2008", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Apr. 14, 2008, pp. 1-7, Published in: EP.

European Patent Office, "Office Action from EP Application No. 06772594.5 mailed Oct. 5, 2009", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Oct. 5, 2009, pp. 1-3, Published in: EP.

European Patent Office, "Office Action from EP Application No. 06772594.5 mailed Nov. 12, 2010", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Nov. 12, 2010, pp. 1-5, Published in: EP.

European Patent Office, "Office Action from EP Application No. 06772594.5 mailed Nov. 3, 2011", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Nov. 3, 2011, pp. 1-3, Published in: EP.

Japan Patent Office, "Notification of Reasons for Rejection from JP Application No. 2008-515931 mailed Nov. 1, 2011", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Nov. 1, 2011, pp. 1-10, Published in: JP.

Japan Patent Office, "Decision of Final Rejection from JP Application No. 2008-515931 mailed Feb. 28, 2012", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Feb. 28, 2012, pp. 1-8, Published in: JP.

Korean Patent Office, "Office Action from KR Application No. 2007-7030470 mailed Sep. 17, 2012", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Sep. 17, 2012, pp. 1-5, Published in: KR.

U.S. Patent and Trademark Office, "Examiner's Answer", "U.S. Appl. No. 12/775,897", Jan. 4, 2013, pp. 1-30.

U.S. Patent and Trademark Office, "Final Office Action", "U.S. Appl. No. 12/775,897", May 7, 2012, pp. 1-26.

U.S. Patent and Trademark Office, "Office Action", "U.S. Appl. No. 12/775,897", Dec. 28, 2011, pp. 1-29.

U.S. Patent and Trademark Office, "Pre-Appeal Brief Decision", "U.S. Appl. No. 12/775,897", Sep. 18, 2012, pp. 1-2.

International Preliminary Examining Authority, "International Preliminary Report on Patentability from PCT Application No. PCT/US2006/022342 mailed Dec. 27, 2007", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Dec. 27, 2007, pp. 1-9, Published in: WO.

International Searching Authority, "International Search Report and Written Opinion from PCT Application No. PCT/US2006/022342 mailed Nov. 7, 2006", "from Foreign Counterpart of U.S. Appl. No. 11/150,820", Nov. 7, 2006, pp. 1-13, Published in: WO.

"DigivanceTM, Indoor Coverage Solution", "www.adc.com", 2001, pp. 1-8, Publisher: ADC.

Grace, Martin K., "Synchronous Quantized Subcarrier Multiplexing for Transport of Video, Voice and Data", "IEEE Journal on Selected Areas in Communications", Sep. 1990, pp. 1351-1358, vol. 8, No. 7, Publisher: IEEE.

Harvey et al., "Cordless Communications Utilising Radio Over Fibre Techniques for the Local Loop", "IEEE International Conference on Communications", Jun. 1991, pp. 1171-1175, Publisher: IEEE.

"Tektronix Synchronous Optical Network (SONET)", "http://www.iec.org/online/tutorials/sonet/topic03.html", Aug. 28, 2002, pp. 1-5, Publisher: International Engineering Consortium.

International Search Authority, "International Preliminary Report on Patentability and Written Opinion for PCT Application No. PCT/US2014/017648", "from Foreign Counterpart to U.S. Appl. No. 14/187,135", Sep. 3, 2015, pp. 1-7, Published in: WO.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C






FIG. 3








FIG. 4C




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

UNIVERSAL REMOTE RADIO HEAD**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. Provisional Patent Application Ser. No. 61/768,038 filed on Feb. 22, 2013, which is hereby incorporated herein by reference.

BACKGROUND

Distributed base stations systems may include base station baseband signal processing functionality and base station control functionality and remote radio heads. Remote radio heads may include radio frequency (RF) transceivers and power amplifiers. In exemplary distributed base station radio systems, digital baseband data is transported between the baseband processing unit located in the host unit and the remotely located radio frequency (RF) transceivers located at the remote units. In exemplary distributed base station radio systems, the baseband processing unit communicates with the remote radio head using channelized Common Public Radio Interface (CPRI) signals and/or Open Base Station Architecture Initiative (OBSAI) signals.

SUMMARY

A distributed base station radio system includes a first channelized to broadband conversion unit configured to receive first downlink channelized data for a first radio frequency band from a first channelized radio frequency source; and a first universal remote radio head communicatively coupled to the first channelized to broadband conversion unit. The first channelized to broadband conversion unit is further configured to convert the first downlink channelized data into a first downlink broadband signal. The first channelized to broadband conversion unit is further configured to communicate the first downlink broadband signal to the first universal remote radio head. The first universal remote radio head is configured to receive the first downlink broadband signal. The first universal remote radio head is further configured to frequency convert the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band. The first universal remote radio head is further configured to transmit the first downlink radio frequency signals in the first radio frequency band to a first subscriber unit.

DRAWINGS

Understanding that the drawings depict only exemplary embodiments and are not therefore to be considered limiting in scope, the exemplary embodiments will be described with additional specificity and detail through the use of the accompanying drawings, in which:

FIGS. 1A-1B are block diagrams of exemplary embodiments of distributed base station radio systems;

FIGS. 2A-2C are block diagrams of exemplary embodiments of channelized broadband conversion units used in distributed base station radio systems, such as the exemplary distributed base station radio systems in FIGS. 1A-1B;

FIG. 3 is a block diagram of an exemplary embodiment of other signal source interfaces used in distributed base station radio systems, such as the exemplary distributed base station radio systems in FIGS. 1A-1B;

FIGS. 4A-4C are block diagrams of exemplary embodiments of distributed base station radio switches used in dis-

2

tributed base station radio systems, such as the exemplary distributed base station radio systems in FIGS. 1A-1B;

FIG. 5 is a block diagram of an exemplary embodiment of a universal remote radio head used in a distributed base station radio system, such as the exemplary distributed base station radio systems in FIGS. 1A-1B;

FIGS. 6A-6E are block diagrams of exemplary embodiments of radio frequency (RF) conversion modules used in universal remote radio heads of distributed base station radio systems, such as the exemplary distributed base station radio systems in FIGS. 1A-1B;

FIG. 7 is a flow diagram illustrating one exemplary embodiment of a method of operating a distributed base station radio system;

FIG. 8 is a flow diagram illustrating another exemplary embodiment of a method of operating a distributed base station radio system;

FIG. 9 is flow diagram illustrating another exemplary embodiment of a method of operating a universal remote radio head; and

FIG. 10 is a flow diagram illustrating another exemplary embodiment of a method of operating a channelized broadband conversion unit.

In accordance with common practice, the various described features are not drawn to scale but are drawn to emphasize specific features relevant to the exemplary embodiments. Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration specific illustrative embodiments. However, it is to be understood that other embodiments may be utilized and that logical, mechanical, and electrical changes may be made. Furthermore, the method presented in the drawing figures and the specification is not to be construed as limiting the order in which the individual steps may be performed. The following detailed description is, therefore, not to be taken in a limiting sense.

The embodiments described below describe a distributed base station radio system including at least one channelized broadband conversion unit communicatively coupled to at least one universal remote radio head. The channelized broadband conversion unit is communicatively coupled to a channelized radio frequency source, usually at a base station. In exemplary embodiments, the channelized broadband conversion unit is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) base station interface. In exemplary embodiments, the channelized broadband conversion source includes a representation of an individual channel at baseband. In exemplary embodiments, the channelized broadband conversion unit converts the representation of the individual channel at baseband into a broadband signal capable of representing a number of individual channels together in a single broadband signal. A broadband signal includes individual channels positioned within a set of spectrum that reflects each channels location within the RF spectrum. When aggregated, the individual channels within the broadband signals do not overlap each other. This broadband signal has a single center frequency while the individual channelized signals each have their own center frequency.

This broadband signal is then distributed through a distributed base station radio switching network to at least one

universal remote radio head. The universal remote radio head is multi-standard and capable of receiving the broadband signal and converting it to radio frequency (RF) and transmitting it using at least one antenna. The universal remote radio head is not specific to a number of channels or an air protocol and does not necessarily require any hardware change when channels are added or removed, or a new modulation type or air protocol is used. In exemplary embodiments, a plurality of channelized broadband conversion units convert a plurality of channelized radio frequency signals received from a plurality of channelized radio frequency sources and representing individual channels into a single broadband signal that is transported through the distributed base station radio switching network to at least one universal remote radio head that converts the single broadband signal into radio frequency (RF) signals and transmits them using at least one antenna. In exemplary embodiments, the at least one universal remote radio head includes a single digital/analog converter and a single RF converter that can up-convert the entire broadband signal into RF spectrum having various channels.

As described herein, channelized signals are specific to a particular channel. In exemplary embodiments, the channelized signals are baseband data, such as channelized in-phase (I) and quadrature (Q) data. The channelized signals are not positioned relative to one another and require additional baseband conversion before RF conversion and transmission can be performed. Specifically, systems that communicate the channelized signals to remote radio heads will require additional processing at the remote radio head to convert the channelized signals before RF conversion and transmission. Accordingly, the remote radio heads are more complex and less flexible than the universal remote radio heads described below.

In contrast, broadband signals are not specific to a particular channel and may include a number of different channels. The broadband signals represent either digitized or analog spectrum and are one step closer to RF signals than the channelized signals. In exemplary embodiments, the broadband signal is at an intermediate frequency that maps to a large portion of RF spectrum including a number of channels. In exemplary embodiments, the broadband signals can simply be up-converted from the intermediate frequency to radio frequency and transmitted at a universal remote radio head as described below. Thus, the universal remote radio heads do not need the capability of processing channelized signals before RF conversion and transmission. Accordingly, universal remote radio heads are less complex. In addition, it doesn't matter what channels are sent to the universal remote radio heads. In exemplary embodiments, the universal remote radio head communicates with subscriber units using a first set of channels at first frequencies and a second set of channels at second frequencies. In exemplary embodiments, the universal remote radio head communicates using different modulation and/or radio access technologies simultaneously.

FIG. 1A-1B are block diagrams of exemplary embodiments of distributed base station radio systems **100**. Each of FIGS. 1A-1B illustrates a different embodiment of a distributed base station radio system **100**, labeled **100A-100B** respectively.

FIG. 1A is a block diagram of an exemplary embodiment of a distributed base station radio system **100**, distributed base station radio system **100A**. Distributed base station radio system **100A** includes at least one channelized broadband conversion unit **102** (including channelized broadband conversion unit **102-1** and any number of optional channelized broadband conversion units **102** through optional channelized broadband conversion unit **102-A**), at least one universal

remote radio head **104** (including universal remote radio head **104-1** and any number of optional universal remote radio heads **104** through optional universal remote radio head **104-B**), a distributed base station radio switching network **106**, and optional other signal source interfaces **108** (including any number of optional other signal source interfaces **108** such as optional other signal source interface **108-1** through optional other signal source interface **108-C**).

Each channelized broadband conversion unit **102** is communicatively coupled to a channelized radio frequency source **110** that is configured to provide a channelized signal representing a single channel to be transported through the distributed base station radio system **100A** to the channelized broadband conversion unit **102-1**. In the forward path, each channelized broadband conversion unit **102** is configured to receive a channelized signal representing a single channel from a corresponding channelized radio frequency source **110**. Specifically, channelized broadband conversion unit **102-1** is communicatively coupled to channelized radio frequency source **110-1** and optional channelized broadband conversion unit **102-A** is communicatively coupled to optional channelized radio frequency source **110-A**. Each channelized broadband conversion unit **102** is also communicatively coupled to the distributed base station radio switching network **106** across a communication link **112**. Specifically, channelized broadband conversion unit **102-1** is communicatively coupled to the distributed base station radio switching network **106** across communication link **112-1** and optional channelized broadband conversion unit **102-A** is communicatively coupled to the distributed base station radio switching network **106** across communication link **112-A**. As described in more detail below, each channelized broadband conversion unit **102** is configured to convert a channelized signal from a corresponding channelized radio frequency source **110** into a downlink broadband signal and further configured to communicate the downlink broadband signal to the distributed base station radio switching network **106** (either directly or through other components of the distributed base station radio system **100A**) across a respective communication link **112**. Each downlink broadband signal contains an individual channel that is positioned within a set of spectrum that reflects its location within the RF spectrum. Said another way, the channel in each downlink broadband signal is at a different RF frequency than the other channels to which it is being aggregated. Thus, when multiple downlink broadband signals are aggregated together, the individual channels do not overlap each other and all channels can be upconverted together to radio frequency spectrum simultaneously.

Similarly in the reverse path, in exemplary embodiments each channelized broadband conversion unit **102** is configured to receive uplink broadband signals across a respective communication link **112** from distributed base station radio switching network **106**. Each channelized broadband conversion unit **102** is further configured to convert the received uplink broadband signal to a channelized signal for the corresponding channelized radio frequency source **110** and is further configured to communicate the channelized signal to the corresponding channelized radio frequency source **110**. In exemplary embodiments, the uplink broadband signal is an aggregate of the uplink broadband signals from at least one universal remote radio head **104**. For example, the uplink broadband signal may be an aggregate of the uplink broadband signals from any number of universal remote radio heads **104**.

In exemplary embodiments, the communication links **112** are optical fibers and the communication across the communication links **112** is optical. In these embodiments, an elec-

trical to optical conversion occurs at the channelized broadband conversion units **102**. In other embodiments, the communication links **112** are conductive cables (such as coaxial cable, twisted pair, etc.) and the communication across the communication links **112** is electrical. In exemplary embodiments, the communication across the communication links **112** is analog communication. In other exemplary embodiments, the communication across the communication links **112** is digital communication. In exemplary embodiments, any mixture of optical, electrical, analog, and digital communication occurs across the communication links **112**. In exemplary embodiments, a channelized broadband conversion unit **102** may include functionality to convert between digital and analog signals.

Distributed base station radio switching network **106** communicatively couples the at least one channelized broadband conversion unit **102** and the optional other signal source interfaces **108** with the at least one universal remote radio head **104**. Distributed base station radio switching network **106** may include one or more distributed base station radio switches or other components that functionally distributes downlink broadband signals from the at least one channelized broadband conversion unit **102** to the at least one universal remote radio head **104**. In exemplary embodiments, the distributed base station radio switching network **106** aggregates downlink broadband signals from a plurality of channelized broadband conversion units **102** into a single aggregate downlink broadband signal that is routed to at least one universal remote radio head **104**. Distributed base station radio switching network **106** also functionally distributes uplink broadband signals from the at least one universal remote radio head **104** to the at least one channelized broadband conversion unit **102**. In exemplary embodiments, the distributed base station radio switching network **106** aggregates uplink broadband signals from a plurality of universal remote radio heads **104** into a single aggregate uplink broadband signal that is routed to at least one channelized broadband conversion unit **102**.

In exemplary embodiments, the communication links **122** between the other signal source interfaces **108** and the distributed base station radio switching network **106** are optical fibers and the communication across the communication links **122** are optical. In these embodiments, an electrical to optical conversion occurs at the other signal source interfaces **108**. In other embodiments, the communication links **122** are conductive cables (such as coaxial cable, twisted pair, etc.) and the communication across the communication links **122** is electrical. In exemplary embodiments, the communication across the communication links **122** is analog communication. In other exemplary embodiments, the communication across the communication links **122** is digital communication. In exemplary embodiments, any mixture of optical, electrical, analog, and digital communication occurs across the communication links **122**. In exemplary embodiments, an other signal source interface **108** may include functionality to convert between digital and analog signals.

Each universal remote radio head **104** is communicatively coupled to the distributed base station radio switching network **106** across a communication link **114**. Specifically, universal remote radio head **104-1** is communicatively coupled to the distributed base station radio switching network **106** across communication link **114-1** and optional universal remote radio head **104-B** is communicatively coupled to the distributed base station radio switching network **106** across communication link **114-B**. Each universal remote radio head **104** includes components configured for converting between at least one downlink broadband signal and at least one radio frequency band signal and at least one

radio frequency antenna **116** configured to transmit and receive signals in the at least one radio frequency band to/from at least one subscriber unit **118**. In exemplary embodiments, the downlink broadband signal is an aggregate of multiple downlink broadband signals each with a channel positioned within a set of spectrum that reflects its location within the RF spectrum. In exemplary embodiments having multiple downlink broadband signals aggregated together, the individual channels can be converted to the at least one radio frequency band signals simultaneously.

In the downstream, each universal remote radio head **104** is configured to convert the at least one downlink broadband signal into a downlink radio frequency (RF) signal in a radio frequency band. In exemplary embodiments, this may include digital to analog converters and oscillators. Each universal remote radio head **104** is further configured to transmit the downlink radio frequency signal in the radio frequency band to at least one subscriber unit **118** using at least one radio frequency antenna **116**. In a specific exemplary embodiment, universal remote radio head **104-1** is configured to convert the at least one downlink broadband signal received from the distributed base station radio switching network **106** into a downlink radio frequency signal in a radio frequency band. Universal remote radio head **104-1** is further configured to transmit the downlink radio frequency signal in a radio frequency band using a radio frequency band antenna **116-1** to at least one subscriber unit **118-1**. In exemplary embodiments, universal remote radio head **104-1** is configured to convert the at least one downlink broadband signal received from the distributed base station radio switching network **106** into a plurality of downlink radio frequency signals in a plurality of radio frequency bands. In these exemplary embodiments, universal remote radio head **104-1** is further configured to transmit the plurality of downlink radio frequency signals in the plurality of radio frequency bands using the radio frequency band antenna **116-1** and optional other radio frequency band antennas **116** through optional other radio frequency band antenna **116-D**. In exemplary embodiments, the universal remote radio head **104-1** is configured to transmit one downlink radio frequency signal to one subscriber unit **118-1** using an antenna **116-1** and another radio frequency signal to one subscriber unit **118-E** using another antenna **116-D**. In exemplary embodiments, other combinations of radio frequency antennas **116** and other components are used to communicate other combinations of radio frequency signals in other various radio frequency bands to various subscriber units **118**, such as but not limited to using multiple antenna to communicate with a single subscriber unit **118**.

Similarly in the reverse path, in exemplary embodiments, each universal remote radio head **104** is configured to receive uplink radio frequency signals from at least one subscriber unit **118** using at least one radio frequency antenna **116**. Each universal remote radio head **104** is further configured to convert the radio frequency signals to at least one uplink broadband signal. Each universal remote radio head **104** is further configured to aggregate the at least one uplink broadband signal into an aggregate uplink broadband signal and further configured to communicate the aggregate uplink broadband signal across at least one communication link **114** to the distributed base station radio switching network. In exemplary embodiments, universal remote radio heads **104** multiplex uplink signals in different bands onto the same interface for communication to the next upstream element. In other exemplary embodiments (such as example embodiments implementing diversity processing), where the universal remote radio head **104** could aggregate (i.e. sum/combine) uplink signals in an intelligent manner. In exemplary embodi-

ments, each uplink broadband signal contains a channel that is positioned within a set of spectrum that reflects its location within the RF spectrum. Thus and even though the uplink broadband signals that are aggregated will overlap in frequency spectrum, the individual channels themselves from the aggregated uplink broadband signals do not overlap each other when multiple uplink broadband signals are aggregated together.

In exemplary embodiments, the communication links **114** are optical fibers and the communication across the communication links **114** is optical. In these embodiments, an electrical to optical conversion occurs at the universal remote radio heads **104**. In other embodiments, the communication links **114** are conductive cables (such as coaxial cable, twisted pair, etc.) and the communication across the communication links **114** is electrical. In exemplary embodiments, the communication across the communication links **114** is analog communication. In other exemplary embodiments, the communication across the communication links **114** is digital communication. In exemplary embodiments, any mixture of optical, electrical, analog, and digital communication occurs across the communication links **114**. In exemplary embodiments, a universal remote radio head **104** may include functionality to convert between digital and analog signals.

FIG. 1B is a block diagram of an exemplary embodiment of a distributed base station radio system **100**, distributed base station radio system **100B**. Distributed base station radio system **100B** includes at least one channelized broadband conversion unit **102** (including channelized broadband conversion unit **102-1** and any number of optional channelized broadband conversion units **102** through optional channelized broadband conversion unit **102-A**), at least one universal remote radio head **104** (including universal remote radio head **104-1** and any number of optional universal remote radio heads **104** through optional universal remote radio head **104-B**), a distributed base station radio switch **124**, and optional other signal source interfaces **108** (including any number of optional other signal source interfaces **108** such as optional other signal source interface **108-1** through optional other signal source interface **108-C**). Distributed base station radio system **100B** includes similar components to distributed base station radio system **100A** described above and operates according to similar principles and methods as distributed base station radio system **100A** described above. The difference between distributed base station radio system **100B** and distributed base station radio system **100A** is that the distributed base station radio switching network **106** is replaced with a single distributed base station radio switch **124**.

Distributed base station radio switch **124** communicatively couples the at least one channelized broadband conversion unit **102** and the optional other signal source interfaces **108** with the at least one universal remote radio head **104**. Distributed base station radio switch **124** functionally distributes downlink broadband signals from the at least one channelized broadband conversion unit **102** to the at least one universal remote radio head **104**. In exemplary embodiments, the distributed base station radio switch **124** aggregates downlink broadband signals from a plurality of channelized broadband conversion units **102** into a single aggregate downlink broadband signal that is routed to at least one universal remote radio head **104**. Distributed base station radio switch **124** also functionally distributes uplink broadband signals from the at least one universal remote radio head **104** to the at least one channelized broadband conversion unit **102** and any optional other signal source interfaces **108**. In exemplary embodiments, the distributed base station radio switch **124** aggregates

uplink broadband signals from a plurality of universal remote radio heads **104** into a single aggregate uplink broadband signal that is routed to at least one channelized broadband conversion unit **102**.

FIGS. 2A-2C are block diagrams of exemplary embodiments of channelized broadband conversion units **102** used in distributed base station radio systems, such as the exemplary distributed base station radio system **100** described above. Each of FIGS. 2A-2C illustrates a different embodiment of a type of base station network interface **102**, labeled **102A-102C** respectively.

FIG. 2A is a block diagram of an exemplary embodiment of a channelized broadband conversion unit **102**, channelized broadband conversion unit **102A**. Channelized broadband conversion unit **102A** includes channelized to broadband conversion module **202A**, an optional processor **204**, optional memory **206**, and an optional power supply **208**. In exemplary embodiments, channelized to broadband conversion module **202A** is communicatively coupled to at least one channelized radio frequency source **110**. Channelized to broadband conversion module **202A** is also communicatively coupled to at least one communication link **112**. In exemplary embodiments, the communication link **112** is an optical communication link across a fiber optic cable, though it can also be other types of wired or wireless links in other embodiments. In exemplary embodiments, the channelized to broadband conversion module **202** is implemented using optional processor **204** and optional memory **206**. In exemplary embodiments, the optional power supply **208** provides power to the various elements of the channelized broadband conversion unit **102A**.

In the downlink, channelized to broadband conversion module **202A** is configured to receive a channelized downlink signal from the channelized radio frequency source **110A**. The channelized to broadband conversion module **202A** is further configured to convert the channelized downlink signal to a downlink broadband signal. In exemplary embodiments, the channelized to broadband conversion module **202** (or another additional component) further converts the downlink broadband signal from electrical signals to optical signals for output on an optical communication link **112**. In other embodiments, the downlink broadband signal is transported using a conductive communication medium, such as coaxial cable or twisted pair, and the optical conversion is not necessary. In exemplary embodiments, the channelized to broadband conversion module **202** (or another additional component) further converts between digital and analog signals as required.

In the uplink, channelized to broadband conversion module **202A** is configured to receive an uplink broadband signal from communication link **112**. In exemplary embodiments where communication link **112** is an optical medium, the channelized to broadband conversion module **202A** (or another additional component) is configured to convert the uplink broadband signal between received optical signals and electrical signals. In other embodiments, the uplink broadband signal is transported using a conductive communication medium, such as coaxial cable or twisted pair, and the optical conversion is not necessary. In exemplary embodiments, the channelized to broadband conversion module **202** (or another additional component) further converts between digital and analog signals as required. The channelized to broadband conversion module **202A** is further configured to convert the uplink broadband signal to at least one uplink channelized signal. Channelized to broadband conversion module **202A** is further configured to communicate the uplink channelized signals to the channelized radio frequency source **110A**.

FIG. 2B is a block diagram of an exemplary embodiment of a channelized broadband conversion unit **102**, Common Public Radio Interface (CPRI) broadband conversion unit **102B**. CPRI broadband conversion unit **102B** includes Common Public Radio Interface (CPRI) to broadband conversion module **202B**, an optional processor **204**, optional memory **206**, and an optional power supply **208**. CPRI broadband conversion unit **102B** includes similar components to channelized broadband conversion unit **102A** and operates according to similar principles and methods as channelized broadband conversion unit **102A**. The difference between CPRI broadband conversion unit **102B** and the channelized broadband conversion unit **102A** is that the CPRI broadband conversion unit **102B** is CPRI specific and includes the CPRI to broadband conversion module **202B** that is communicatively coupled to at least one Common Public Radio Interface (CPRI) source **110B**. CPRI broadband conversion unit **102B** converts between CPRI channelized signals and broadband signals. In the downlink, CPRI broadband conversion unit **102B** converts downlink CPRI channelized signals into a downlink broadband signal. In the uplink, CPRI broadband conversion unit **102B** converts an uplink broadband signal into uplink CPRI channelized signals.

FIG. 2C is a block diagram of an exemplary embodiment of a channelized broadband conversion unit **102**, Open Base Station Architecture Initiative (OBSAI) broadband conversion unit **102C**. OBSAI broadband conversion unit **102C** includes Open Base Station Architecture Initiative (OBSAI) to broadband conversion module **202C**, an optional processor **204**, optional memory **206**, and an optional power supply **208**. OBSAI broadband conversion unit **102C** includes similar components to channelized broadband conversion unit **102A** and operates according to similar principles and methods as channelized broadband conversion unit **102A**. The difference between OBSAI broadband conversion unit **102C** and the channelized broadband conversion unit **102A** is that the OBSAI broadband conversion unit **102C** is OBSAI specific and includes the OBSAI to broadband conversion module **202C** that is communicatively coupled to at least one Open Base Station Architecture Initiative (OBSAI) source **110C**. OBSAI broadband conversion unit **102C** converts between OBSAI channelized signals and broadband signals. In the downlink, OBSAI broadband conversion unit **102C** converts downlink OBSAI channelized signals into a downlink broadband signal. In the uplink, OBSAI broadband conversion unit **102C** converts an uplink broadband signal into uplink OBSAI channelized signals.

FIG. 3 is a block diagram of an exemplary embodiment of other signal source interface **108** used in distributed base station radio systems, such as the exemplary distributed base station radio system **100**. Other signal source interface **108** includes a signal source to broadband signal conversion module **302**, an optional processor **304**, optional memory **306**, and an optional power supply **308**. In exemplary embodiments, signal source to broadband conversion module **302** is communicatively coupled to at least one other signal source **120**. Signal source to broadband conversion module **302** is also communicatively coupled to at least one communication link **122**. In exemplary embodiments, the communication link **122** is an optical communication link across a fiber optic cable, though it can also be other types of wired or wireless links in other embodiments. In exemplary embodiments, the signal source to broadband conversion module **302** is implemented using optional processor **304** and optional memory **306**. In exemplary embodiments, the optional power supply **308** provides power to the various elements of the other signal source interface **302**.

In the downlink, signal source to broadband conversion module **302** is configured to receive a downlink signal from the other signal source **120**. The signal source to broadband signal conversion module **302** is further configured to convert the downlink signal to a downlink broadband signal. In exemplary embodiments, the signal source to broadband signal conversion module **302** (or another additional component) is further configured to convert the downlink broadband signal from electrical signals to optical signals for output on an optical communication link **122**. In other embodiments, the downlink broadband signal is transported using a conductive communication medium, such as coaxial cable or twisted pair, and the optical conversion is not necessary. In exemplary embodiments, the signal source to broadband signal conversion module **302** (or another additional component) further converts between digital and analog signals as required.

In the uplink, signal source to broadband signal conversion module **302** is configured to receive an uplink broadband signal from communication link **122**. In exemplary embodiments where communication link **122** is an optical medium, the signal source to broadband signal conversion module **302** (or another additional component) is configured to convert the uplink broadband signal between received optical signals and electrical signals. In other embodiments, the uplink broadband signal is transported using a conductive communication medium, such as coaxial cable or twisted pair, and the optical conversion is not necessary. In exemplary embodiments, the signal source to broadband signal conversion module **302** (or another additional component) further converts between digital and analog signals as required. The signal source to broadband signal conversion module **302** is further configured to convert the uplink broadband signal to at least one uplink signal. Signal source to broadband signal conversion module **302** is further configured to communicate the uplink signals to the other signal source **120**.

FIGS. 4A-4C are block diagrams of exemplary embodiments of distributed base station radio switch **124** used in distributed base station radio systems, such as the exemplary distributed base station radio system **100** described above. Each of FIGS. 4A-4C illustrates a different embodiment of distributed base station radio system **100**, labeled distributed base station radio switch **124A-124C** respectively.

FIG. 4A is a block diagram of an exemplary distributed base station radio switch **124A** including a routing unit **402**, at least one electro-optical conversion module **404-1** (including electro-optical conversion module **404-1** and any amount of optional electro-optical conversion modules **404** through electro-optical conversion module **404-A**), at least one electro-optical conversion module **406-1** (including electro-optical conversion module **406-1** through optional electro-optical conversion module **406-B**), and optional electro-optical conversion modules **408-1** (including optional electro-optical conversion module **408-1** through optional electro-optical conversion module **408-C**). In exemplary embodiments, the routing unit **402** and/or at least a portion of any of electro-optical conversion modules **404**, electro-optical conversion modules **406**, and electro-optical conversion modules **408** are implemented using optional processor **410** and memory **412**. In exemplary embodiments, the distributed base station radio switch **124A** includes optional power supply **414** to power the various components of the distributed base station radio switch **124A**.

Each electro-optical conversion module **404** is communicatively coupled to a channelized broadband conversion unit **102** across a communication link **112**. In the forward path, each electro-optical conversion module **404** is configured to receive a downlink broadband signal from at least one chan-

11

nelized broadband conversion unit **102** across a communication link **112**. Specifically, electro-optical conversion module **404-1** is configured to receive a downlink broadband signal from the channelized broadband conversion unit **102-1** across communication link **112-1** and optional electro-optical conversion module **404-A** is configured to receive a downlink broadband signal from the optional channelized broadband conversion unit **102-A** across optional communication link **112-A**. Each electro-optical conversion module **404** is configured to convert the downlink broadband signal from optical to electrical signals, which are then passed onto the routing unit **402**. Similarly in the reverse path, in exemplary embodiments each electro-optical conversion module **404** is configured to receive an uplink broadband signal in an electrical format from the routing unit **402** and to convert the uplink broadband signal to an optical format for communication across a communication link **112** to a channelized broadband conversion unit **102**. In exemplary embodiments, the electro-optical conversion module **404** (or another additional component) further converts between digital and analog signals as required.

Each optional electro-optical conversion module **408** is communicatively coupled to an optional other signal source interface **108** across a communication link **122**. In the forward path, each electro-optical conversion module **408** is configured to receive a downlink broadband signal from at least one other signal source interface **108** across a communication link **122**. Specifically, optional electro-optical conversion module **408-1** is configured to receive a downlink broadband signal from the optional other signal source interface **108-1** across optional communication link **122-1** and optional electro-optical conversion module **408-C** is configured to receive a downlink broadband signal from the optional other signal source interface **108-C** across optional communication link **122-C**. Each electro-optical conversion module **408** is configured to convert the downlink broadband signal from optical to electrical signals, which are then passed onto the routing unit **402**. Similarly in the reverse path, in exemplary embodiments each electro-optical conversion module **408** is configured to receive an uplink broadband signal in an electrical format from the routing unit **402** and to convert the uplink broadband signal to an optical format for communication across a communication link **112** to an other signal source interface **108**. In exemplary embodiments, the electro-optical conversion module **408** (or another additional component) further converts between digital and analog signals as required.

The routing unit **402** is communicatively coupled between at least one electro-optical conversion module **404** and optional electro-optical conversion module **408** and at least one electro-optical conversion module **406**. The routing unit **402** routes downlink broadband signals and uplink broadband signals between various electro-optical conversion modules **404**, electro-optical conversion modules **408**, and electro-optical conversion modules **406**. In the forward path, the routing unit **402** receives downlink broadband signals for at least one electro-optical conversion module **404** and any optional electro-optical conversion modules **408** and routes these downlink broadband signals to at least one electro-optical conversion module **406** (such as electro-optical conversion module **406-1**) for eventual transmission to a universal remote radio head **104**.

In exemplary embodiments, this routing includes aggregation of a plurality of downlink broadband signals from a plurality of electro-optical conversion modules **404** and/or electro-optical conversion modules **408** into a single downlink broadband signal that is passed to at least one electro-

12

optical conversion module **406**. In exemplary embodiments, the same or different downlink aggregate broadband signals are routed to a plurality of electro-optical conversion modules **406**. In some embodiments, the routing unit **402** is configured to aggregate and route downlink broadband signals from a first subset of channelized broadband conversion units **102** and/or other signal source interfaces **108** into a first downlink aggregate broadband signal that is transferred to at least a first universal remote radio head **104-1** via electro-optical conversion module **406-1** and communication link **114-1** and is further configured to aggregate and route downlink broadband signals from a second subset of channelized broadband conversion units **102** and/or other signal source interfaces **108** into a second downlink aggregate broadband signal that is transferred to at least a second universal remote radio head **104-B** via electro-optical conversion module **406-B** and communication link **114-B**. In exemplary embodiments, the first and second subsets partially overlap. In other exemplary embodiments, the first and second subsets are identical. In other exemplary embodiments, downlink broadband signals from greater number of subsets of channelized broadband conversion units **102** and other signal source interfaces **108** are aggregated and transferred to the universal remote radio head **104**.

In exemplary embodiments, this routing includes separation of a single aggregate downlink broadband signal from a single electro-optical conversion module **404** into a plurality of downlink broadband signals that are passed to a plurality of electro-optical conversion modules **406**. In exemplary embodiments, the same or different downlink broadband signals are routed to a plurality of electro-optical conversion modules **406**. In some embodiments, the routing unit **402** is configured to separate and route downlink broadband signals destined for a first subset of universal remote radio heads **104** from a first downlink aggregate broadband signal received from a single channelized broadband conversion unit **102** (such as channelized broadband conversion unit **102-1**) and is further configured to separate and route downlink broadband signals destined for a second subset of universal remote radio heads **104** from a second downlink aggregate broadband signal received from a second channelized broadband conversion unit **102** (such as channelized broadband conversion unit **102-A**). In exemplary embodiments, the first and second subsets partially overlap. In other exemplary embodiments, the first and second subsets are identical. In other exemplary embodiments, downlink broadband signals are destined to greater number of subsets of universal remote radio heads **104**.

Similarly in the reverse path, the routing unit **402** receives at least one uplink broadband signal from at least one electro-optical conversion module **406** (such as electro-optical conversion module **406-1**) from a universal remote radio head **104** and routes the at least one uplink broadband signal to at least one electro-optical conversion module **404** (such as electro-optical conversion module **404-1**) for eventual communication to a channelized broadband conversion unit **102**. In exemplary embodiments, this routing includes aggregation of a plurality of uplink broadband signals from a plurality of electro-optical conversion modules **406** into a single uplink broadband signal that is passed to at least one electro-optical conversion module **404**. In exemplary embodiments, the same or different uplink aggregate broadband signals are routed to a plurality of electro-optical conversion modules **404** and/or optional electro-optical conversion modules **408**. In some embodiments, the routing unit **402** is configured to aggregate and route uplink broadband signals from a first subset of universal remote radio heads **104** into a first uplink

13

aggregate broadband signal that is transferred to at least a first channelized broadband conversion unit **102-1** via electro-optical conversion module **404-1** and communication link **112-1** and is further configured to aggregate and route uplink broadband signals from a second subset of universal remote radio heads **104** into a second uplink aggregate broadband signal that is transferred to at least a second channelized broadband conversion unit **102-A** via second electro-optical conversion module **404-A** and communication link **112-A**. In exemplary embodiments, the first and second subsets partially overlap. In other exemplary embodiments, the first and second subsets are identical. In other exemplary embodiments, uplink broadband signals are aggregated and/or routed from a greater number of subsets of universal remote radio heads **104**.

In exemplary embodiments, this routing includes separation of a single aggregate uplink broadband signal from a single universal remote radio head **104** into a plurality of uplink broadband signals that are passed to a plurality of electro-optical conversion modules **404** and/or electro-optical conversion modules **208-1**. In exemplary embodiments, the same or different uplink broadband signals are routed to a plurality of electro-optical conversion modules **404**. In some embodiments, the routing unit **402** is configured to separate and route uplink broadband signals destined for a first set of channelized broadband conversion units **102** from a first aggregate uplink broadband signal received from a single universal remote radio head **104** (such as universal remote radio head **104-1**) and is further configured to separate and route uplink broadband signals destined for a second subset of channelized broadband conversion units **102** from a second aggregate uplink broadband signal received from a second universal remote radio head **104** (such as universal remote radio head **104-B**). In exemplary embodiments, the first and second subsets partially overlap. In other exemplary embodiments, the first and second subsets are identical. In other exemplary embodiments, uplink broadband signals are destined to greater number of subsets of channelized broadband conversion units **102** and/or other signal source interfaces **108**.

In exemplary embodiments, this routing includes aggregation of a plurality of uplink broadband signals from a plurality of universal remote radio heads **104** via a plurality of electro-optical conversion modules **406** into a single aggregate uplink broadband signal that is passed to at least one channelized broadband conversion unit **102** through at least one electro-optical conversion module **404**. In exemplary embodiments, the same or different uplink aggregate broadband signals are routed to a plurality of electro-optical conversion modules **406**. In some embodiments, the routing unit **402** is configured to aggregate and route uplink broadband signals from a first subset of universal remote radio heads **104** into a first uplink aggregate broadband signal that is transferred to at least a first channelized broadband conversion unit **102-1** via electro-optical conversion module **404-1** and communication link **112-1** and is further configured to aggregate and route uplink broadband signals from a second subset of universal remote radio heads **104** into a second uplink aggregate broadband signal that is transferred to at least a second channelized broadband conversion unit **102-A** via electro-optical conversion module **404-A** and communication link **112-A**. In exemplary embodiments, the first and second subsets partially overlap. In other exemplary embodiments, the first and second subsets are identical. In other exemplary embodiments, uplink broadband signals from a greater number of subsets of universal remote radio heads **104** are aggregated and trans-

14

ferred to channelized broadband conversion units **102** and other signal source interfaces **108**.

The electrical and optical signals communicated between the channelized broadband conversion units **102**, other signal source interfaces **108**, universal remote radio heads **104**, the distributed base station radio switch **124A**, and within the distributed base station radio switch **124A** can be any combination of digital and analog signals. In exemplary embodiments, these electrical signals are digital signals. In other exemplary embodiments, these electrical signals are analog signals. In other exemplary embodiments, these electrical signals include a combination of digital and analog signals. In exemplary implementations, the communication between one or more channelized broadband conversion units **102** and the distributed base station radio switch **124A** is digital and the communication between the distributed base station radio switch **124A** and one or more universal remote radio heads **104** is analog. In exemplary implementations, the communication between one or more channelized broadband conversion units **102** and the distributed base station radio switch **124A** is analog and the communication between the distributed base station radio switch **124A** and one or more universal remote radio heads **104** is digital. In exemplary implementations, the communication between a first subset of the channelized broadband conversion units **102** and/or other signal source interfaces **108** and the distributed base station radio switch **124A** is digital and the communication between a second subset of the channelized broadband conversion units **102** and/or other signal source interfaces **108** and the distributed base station radio switch **124A** is analog. In exemplary implementations, the communication between the distributed base station radio switch **124A** and a first set of universal remote radio heads **104** is digital while the communication between the distributed base station radio switch **124A** and a second set of universal remote radio heads **104** is analog. Accordingly, in exemplary embodiments the routing unit **402** includes functionality to convert between digital and analog signals as appropriate.

FIG. 4B is a block diagram of an exemplary distributed base station radio switch **124B** including a routing unit **402**. In exemplary embodiments, the routing unit **402** is implemented using optional processor **410** and memory **412**. Exemplary distributed base station radio switch **124B** includes similar components to distributed base station radio switch **124A** and operates according to similar principles and methods as distributed base station radio switch **124A** described above. The difference between distributed base station radio switch **124B** and distributed base station radio switch **124A** is that distributed base station radio switch **124B** does not include any electro-optical conversion modules because the signals between the channelized broadband conversion units **102**, the other signal source interfaces **108**, and the universal remote radio heads **104** are communicated as electrical signals and not optical signals and do not need to be converted to and from optical signals. As described above, these electrical and optical signals can be any combination of digital and analog signals.

FIG. 4C is a block diagram of an exemplary distributed base station radio switch **124C** including a routing unit **402** and at least one electro-optical conversion module **406** (including electro-optical conversion module **406-1** and any amount of optional electro-optical conversion modules **406** through electro-optical conversion module **406-B**). In exemplary embodiments, the routing unit **402** and/or some portion of the functionality of at least one electro-optical conversion module **406** is implemented using optional processor **410** and memory **412**. Exemplary distributed base station radio switch

15

124C includes similar components to distributed base station radio switch 124A and operates according to similar principles and methods as distributed base station radio switch 124A described above. The difference between distributed base station radio switch 124C and distributed base station radio switch 124A is that distributed base station radio switch 124C does not include electro-optical conversion modules 404 between the channelized broadband conversion units 102 and the routing unit 402 or the other signal source interfaces 108 and the routing unit 402 because the signals between routing unit 402, the channelized broadband conversion units 102, and the other signal source interfaces 108 are communicated as electrical signals and are not optical signals and do not need to be converted to and from optical signals. As described above, these electrical and optical signals can be any combination of digital and analog signals.

FIG. 5 is a block diagram of an exemplary embodiment of a universal remote radio head 104 used in a distributed base station radio system 100. The universal remote radio head 104 includes a multiplexing unit 502, at least one radio frequency (RF) conversion module 504-1 (including RF conversion module 504-1 and any amount of optional RF conversion modules 504 through optional conversion module 504-C), optional electro-optical conversion module 506, optional Ethernet interface 508, optional processor 510, optional memory 512, and optional power supply 514. In exemplary embodiments, multiplexing unit 502, at least one RF conversion module 504, optional electro-optical conversion module 506, and/or optional Ethernet interface 508 are implemented at least in part by optional processor 510 and memory 512 of universal remote radio head 104. In exemplary embodiments, the optional power supply 514 powers the various components of universal remote radio head 105.

The optional electro-optical conversion module 506 is communicatively coupled to the universal remote radio head switching network 106 across a communication link 114. In the forward path, the optional electro-optical conversion module 506 is configured to receive a downlink broadband signal from the distributed base station radio switching network 106 and/or the distributed base station radio switch 124 across a communication link 114. The optional electro-optical conversion module 506 is configured to convert the downlink broadband signal from optical to electrical format, which is then passed onto the multiplexing unit 502. Similarly, in the reverse path, in exemplary embodiments the optional electro-optical conversion module 506 is configured to receive an uplink broadband signal from the multiplexing unit 502. The optional electro-optical conversion module 506 is further configured to convert the uplink broadband signal from electrical to optical format, which is then passed onto the distributed base station radio switching network 106 and/or the distributed base station radio switch 124 across the communication link 114. In exemplary embodiments, more than one electro-optical conversion module 506 is coupled across more than one communication link 114 to the same distributed base station radio switch 124, an intermediary device, and/or another distributed base station radio switch 124. In exemplary embodiments that do not include the electro-optical conversion module 506, the signals communicated between the universal remote radio head 104 and the distributed base station radio switching network 106 and/or the distributed base station radio switch 124 are electrical signals and do not require any conversion between optical and electrical. In exemplary embodiments, the electro-optical conversion module 506 (or another additional component) further converts between digital and analog signals as required.

16

The multiplexing unit 502 is communicatively coupled between the electro-optical conversion module 506 and/or the distributed base station radio switching network 106 and the at least one RF conversion module 504 and the optional Ethernet interface 508. In the forward path, the multiplexing unit 502 is configured to receive a downlink broadband signal from the distributed base station radio switching network 106 and/or a distributed base station radio switch 124 directly or via the optional electro-optical conversion module 506. In exemplary embodiments, the multiplexing unit 502 simulates the broadband signal to each RF conversion module 504. In other embodiments, the multiplexing unit 502 splits apart individual downlink broadband signals from a downlink aggregate broadband signal and passes them to a plurality of RF conversion modules 504. In exemplary embodiments, one of the downlink broadband signals communicated to one of the RF conversion modules 504 pertains to a first mobile access band and/or technology while another downlink broadband signal communicated to another one of the RF conversion modules 504 pertains to a second mobile access band and/or technology. In exemplary embodiments, the multiplexing unit 502 splits off a signal and communicates it to the Ethernet interface 508. In exemplary embodiments, other types of data are carried in the downlink broadband signals.

Similarly in the reverse path, the multiplexing unit 502 is configured to receive upstream signals from various radio frequency (RF) conversion modules 504 and is further configured to multiplex a plurality of upstream signals into a single uplink broadband signal. In exemplary embodiments, the multiplexing unit 502 is configured to aggregate a plurality of upstream signals from various radio frequency (RF) conversion modules 504 into a single uplink broadband signal. The multiplexing unit 502 is further configured to communicate the uplink broadband signal to distributed base station radio switching network 106 and/or the distributed base station radio switch 124 directly or via the optional electro-optical conversion module 506.

Each RF conversion module 504 is communicatively coupled to the multiplexing unit 502 and is coupled to and/or includes at least one antenna 116. Each RF conversion module 504 is configured to convert between at least one downlink broadband signal and radio frequency signals in at least one radio frequency band. Each RF conversion module is configured to communicate radio frequency signals in the at least one radio frequency band across an air medium with at least one subscriber using at least one antenna 116.

In the downstream, each RF conversion module 504 is configured to convert at least one downlink signal into a downlink radio frequency (RF) signal in a radio frequency band. In exemplary embodiments, this may include digital to analog converters and oscillators. Each RF conversion module 504 is further configured to transmit the downlink radio frequency signals in the radio frequency band to at least one subscriber unit 118 using at least one antenna 116. In a specific embodiment, radio frequency conversion module 504-1 is configured to convert at least one downlink broadband signal into a downlink radio frequency signal in a radio frequency band. Each RF conversion module 504 is further configured to transmit the downlink radio frequency signal in a radio frequency band using a radio frequency antenna 116-1 to at least one wireless subscriber unit. In exemplary embodiments, radio frequency conversion module 504-1 is configured to convert a first downlink signal into a first downlink radio frequency signal in a first radio frequency band and to transmit the first downlink radio frequency signal in the first radio frequency band to at least one wireless subscriber using the antenna 116-1. Similarly, radio frequency conversion

17

module **504-2** is configured to convert a second downlink broadband signal into a second downlink radio frequency signal in a second radio frequency band and to transmit the second downlink radio frequency signal in the second radio frequency band to at least one wireless subscriber unit **118** using the antenna **116-2**. In exemplary embodiments, one radio frequency conversion module **504-1** and antenna **116-1** pair transports to a first set of wireless subscriber units **118** in a first band and another radio frequency conversion module **504-C** and antenna **116-C** pair transports to a second set of wireless subscriber units **118** in a second band. Other combinations of radio frequency conversion module **504** and antenna **116** pairs are used to communicate other combinations of radio frequency signals in other various radio frequency bands to various subscriber units **118**, such as but not limited to MIMO or carrier aggregation where signals from multiple antennas go to a single subscriber unit **118**.

Similarly in the reverse path, in exemplary embodiments each RF conversion module **504** is configured to receive uplink radio frequency signals from at least one subscriber unit **118** using at least one radio frequency antenna **116**. Each radio frequency conversion module **504** is further configured to convert the radio frequency signals to at least one uplink broadband signal. Each radio frequency conversion module **504** is further configured to communicate the uplink broadband signal to the broadband signal multiplexing unit **502**.

FIGS. **6A-6E** are block diagrams of exemplary embodiments of radio frequency (RF) conversion modules of remote antenna units **106** used in distributed antenna systems, such as exemplary distributed antenna system **100** described above. Each of FIGS. **6A-6E** illustrates a different embodiment of RF conversion module **504**, labeled RF conversion module **504A-504E** respectively.

FIG. **6A** is a block diagram of an exemplary RF conversion module **504A** including an optional signal stream conditioner **602**, an RF frequency converter **604**, an optional RF conditioner **606**, and an RF duplexer **608** coupled to a single antenna **116**.

The optional signal conditioner **602** is communicatively coupled to a multiplexing unit **502** and the radio frequency (RF) converter **604**. In the forward path, the optional signal conditioner **602** conditions the downlink broadband signal (for example, through amplification, attenuation, and filtering) received from the remote multiplexing unit **502** and passes the downlink signal to the RF converter **604**. In the reverse path, the optional signal conditioner **602** conditions the uplink broadband signal (for example, through amplification, attenuation, and filtering) received from the RF converter **604** and passes the uplink broadband signal to the remote multiplexing unit **502**.

The RF converter **604** is communicatively coupled to either the multiplexing unit **502** or the optional signal conditioner **602** on one side and to either RF duplexer **608** or the optional RF conditioner **606** on the other side. In the downstream, the RF converter **604** converts a downlink broadband signal to downlink radio frequency (RF) signals and passes the downlink RF signals onto either the RF duplexer **608** or the optional RF conditioner **606**. In the upstream, the RF converter **604** converts uplink radio frequency (RF) signals received from either the RF duplexer **608** or the optional RF conditioner **606** to an uplink broadband signal and passes the uplink broadband signal to either the multiplexing unit **502** or the optional signal conditioner **602**.

The optional RF conditioner **606** is communicatively coupled between the RF converter **604** and the RF duplexer

18

608. In exemplary embodiments, the RF conditioner **606** performs gain adjustment and filtering on the downstream and upstream RF signals.

The RF duplexer **608** is communicatively coupled to either the RF frequency converter **604** or the optional RF conditioner **606** on one side and the antenna **116** on the other side. The RF duplexer **608** duplexes the downlink RF signals with the uplink RF signals for transmission/reception using the antenna **116**.

FIG. **6B** is a block diagram of an exemplary RF conversion module **504B** including an optional signal conditioner **602**, an RF frequency converter **604**, an optional RF conditioner **606** coupled to a downlink antenna **116A** and an uplink antenna **116B**. RF conversion module **504B** includes similar components to RF conversion module **504A** and operates according to similar principles and methods as RF conversion module **504A** described above. The difference between RF conversion module **504B** and RF conversion module **504A** is that RF conversion module **504B** does not include RF duplexer **608** and instead includes separate downlink antenna **116A** used to transmit RF signals to at least one subscriber unit **118** and uplink antenna **116B** used to receive RF signals from at least one subscriber unit **118**.

FIG. **6C** is a block diagram of an exemplary RF conversion module **504C-1** and exemplary RF conversion module **504C-2** that share a single antenna **116** through an RF duplexer **610**. The RF conversion module **504C-1** includes an optional signal conditioner **602-1** an RF frequency converter **604-1**, an optional RF conditioner **606-1**, and an RF duplexer **608-1** communicatively coupled to RF duplexer **610** that is communicatively coupled to antenna **116**. Similarly, the RF conversion module **504C-2** includes an optional signal conditioner **602-2**, an RF frequency converter **604-2**, an optional RF conditioner **606-2**, and an RF duplexer **608-2** communicatively coupled to RF duplexer **610** that is communicatively coupled to antenna **116**. Each of RF conversion module **504C-1** and **504C-2** operate according to similar principles and methods as RF conversion module **504A** described above. The difference between RF conversion modules **504C-1** and **504C-2** and RF conversion module **504A** is that RF conversion modules **504C-1** and **504C-2** are both coupled to a single antenna **116** through RF duplexer **610**. The RF duplexer **610** duplexes the duplexed downlink and uplink signals for both RF conversion module **504C-1** and **504C-2** for transmission/reception using the single antenna **116**.

FIG. **6D** is a block diagram of an exemplary RF conversion module **504D** including an optional signal conditioner **602**, an RF frequency converter **604**, an optional RF conditioner **606**, and a time division duplexing (TDD) switch **612** coupled to an antenna **116**. RF conversion module **504D** includes similar components to RF conversion module **504A** and operates according to similar principles and methods as RF conversion module **504A** described above. The difference between RF conversion module **504D** and RF conversion module **504A** is that RF conversion module **504D** does not include RF duplexer **608** and instead includes the TDD switch **612** that allows the RF conversion module **504D** to switch between transmit and receive modes at different times based on a TDD signal that can be supplied from other components in the system.

FIG. **6E** is a block diagram of an exemplary RF conversion module **504E-1** and exemplary RF conversion module **504E-2** that share a single antenna **116** through an RF duplexer **610**. The RF conversion module **504E-1** includes an optional signal conditioner **602-1**, an RF frequency converter **604-1**, an optional RF conditioner **606-1**, and a TDD switch **612-1** communicatively coupled to RF duplexer **610** that is

communicatively coupled to antenna 116. Similarly, the RF conversion module 504E-2 includes an optional signal conditioner 602-2, an RF frequency converter 604-2, an optional RF conditioner 606-2, and a TDD switch 612-2 communicatively coupled to RF diplexer 610 that is communicatively coupled to antenna 116. Each of RF conversion module 504E-1 and 504E-2 operate according to similar principles and methods as RF conversion modules 504C-1 and 504C-2 described above. The difference between RF conversion modules 504E-1 and 504E-2 and RF conversion modules 504C-1 and 504C-2 is that RF conversion modules 504E-1 and 504E-2 do not include RF duplexers 608-1 and 608-2 and instead include TDD switches 612-1 and 612-2 that allow the RF conversion modules 504E-1 and 504E-2 to switch between transmit and receive modes based on TDD signals that can be supplied from other components in the system.

FIG. 7 is a flow diagram illustrating an exemplary embodiment of a method 700 of operating a distributed base station radio system. Exemplary method 700 begins at block 702 with receiving a first downlink channelized signal for a first radio frequency band from a first channelized radio frequency source at a first channelized to broadband conversion unit. In exemplary embodiments, the channelized radio frequency source is a base band unit of a wireless access base station. In exemplary embodiments, the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface and an Open Base Station Architecture Initiative (OBSAI) base station interface. In exemplary embodiments, the first downlink channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard and an Open Base Station Architecture Initiative (OBSAI) standard. Exemplary method 700 proceeds to block 704 with converting the first downlink channelized signal into a first downlink broadband signal at the first channelized to broadband conversion unit. Exemplary method 700 proceeds to block 706 with communicating the first downlink broadband signal to a first universal remote radio head from the first channelized to broadband conversion unit 706. Exemplary method 700 proceeds to block 708 with frequency converting the first downlink broadband signal into a first downlink radio frequency signal at the first universal remote radio head. Exemplary method 700 proceeds to block 710 with transmitting a first downlink radio frequency signal in the first radio frequency band to a first subscriber unit at the first universal remote radio head.

In exemplary embodiments, the method 700 further includes receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit. In exemplary embodiments, the method 700 further includes receiving the first downlink broadband signal from the first channelized to broadband conversion unit at a switch; receiving the second downlink broadband signal from the second channelized to broadband conversion unit at the switch; aggregating the first downlink broadband signal with the second downlink broadband signal into an aggregate downlink broadband signal; and communicating the aggregate downlink broadband signal from the switch to the first universal remote radio head.

In exemplary embodiments, the method 700 further includes extracting the first downlink broadband signal from the aggregate downlink broadband signal at the first universal remote radio head.

In exemplary embodiments, the method 700 further includes receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband con-

version unit; converting the second downlink channelized data into a second downlink broadband signal; communicating the second downlink broadband signal to the first universal remote radio head from the second channelized to broadband conversion unit; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band at the first universal remote radio head; and transmitting the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit at the first universal remote radio head.

In implementations, frequency converting the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head; transmitting the first downlink radio frequency signals in the first radio frequency band to a first subscriber unit at the first universal remote radio head occurs at a first power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head; and transmitting the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit at the first universal remote radio head occurs at a second power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head.

In implementations, frequency converting the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head; and transmitting both the first downlink radio frequency signals in the first radio frequency band and the second downlink radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

In implementations, frequency converting both the first downlink broadband signal into the first downlink radio frequency signals in the first radio frequency band and the second downlink broadband signals into the second downlink radio frequency signals in the second radio frequency band occurs at a single radio frequency converter; and transmitting both the first downlink radio frequency signals in the first radio frequency band and the second downlink radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

In exemplary embodiments, the method 700 further includes receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit; converting the second downlink channelized data into a second downlink broadband signal; communicating the second downlink broadband signal to a second universal remote radio head from the second channelized to broadband conversion unit; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band at the second universal remote radio head; and transmitting the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit at the second universal remote radio head.

21

FIG. 8 is a flow diagram illustrating an exemplary embodiment of a method **800** of operating a distributed base station radio system. Exemplary method **800** begins at block **802** with receiving a first uplink radio frequency signal in a first radio frequency band from a first subscriber unit at a first universal remote radio head. Exemplary method **800** proceeds to block **804** with frequency converting the first uplink radio frequency signal in the first radio frequency band into a first uplink broadband signal at a first universal remote radio head **804**. Exemplary method **800** proceeds to block **806** with communicating the first uplink broadband signal to a first channelized to broadband conversion unit from the first universal remote radio head. Exemplary method **800** proceeds to block **808** with converting the first uplink broadband signal into a first uplink channelized signal for the first radio frequency band at the first channelized to broadband conversion unit **808**. Exemplary method **800** proceeds to block **810** with communicating the first uplink channelized signal for the first radio frequency band to the first channelized radio frequency source at the first channelized to broadband conversion unit.

FIG. 9 is a flow diagram illustrating an exemplary embodiment of a method **900** of operating a universal remote radio head. Exemplary method **900** begins at block **902** with receiving a downlink broadband signal having data for a radio frequency band from a remote channelized to broadband conversion module at the universal remote radio head. Exemplary method **900** proceeds to block **904** with frequency converting the downlink broadband signal into a downlink radio frequency signal in the radio frequency band at the universal remote radio head. Exemplary method **900** proceeds to block **906** with transmitting the downlink radio frequency signal in the radio frequency band to a subscriber unit at the universal remote radio head. Exemplary method **900** proceeds to block **908** with receiving an uplink radio frequency signal in the radio frequency band from the subscriber unit at the universal remote radio head. Exemplary method **900** proceeds to block **910** with frequency converting the uplink radio frequency signal in the radio frequency band into an uplink broadband signal at the universal remote radio head. Exemplary method **900** proceeds to block **912** with communicating the uplink broadband signal to the remote channelized to broadband conversion module at the universal remote radio head.

FIG. 10 is a flow diagram illustrating an exemplary embodiment of a method **1000** of operating a channelized to broadband conversion unit. Exemplary method **1000** begins at block **1002** with receiving a downlink channelized signal for a radio frequency band from a channelized radio frequency source at a channelized to broadband conversion unit. In exemplary embodiments, the channelized radio frequency source is a base band unit of a wireless access base station. In exemplary embodiments, the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) base station interface. In exemplary embodiments, the first downlink channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard. Exemplary method **1000** proceeds to block **1004** with converting the downlink channelized signal into a downlink broadband signal at the channelized to broadband conversion unit. Exemplary method **1000** proceeds to block **1006** with communicating the downlink broadband signal to a universal remote radio head at the channelized to broadband conversion unit. Exemplary method **1000** proceeds to block **1008** with receiving an uplink

22

broadband signal from the universal remote radio head at the channelized to broadband conversion unit. Exemplary method **1000** proceeds to block **1010** with converting the uplink broadband signal into an uplink channelized signal for the radio frequency band at the channelized to broadband conversion unit. Exemplary method **1000** proceeds to block **1012** with communicating the uplink channelized signal to the channelized radio frequency source at the channelized to broadband conversion unit.

Embodiments of processors described herein (such as any of processor **204**, processor **304**, processor **410**, and processor **510** described above) include or function with software programs, firmware or other computer readable instructions for carrying out various methods, process tasks, calculations, and control functions, used in the components of the systems described above.

These instructions are typically stored on any appropriate computer readable medium used for storage of computer readable instructions or data structures. The computer readable medium can be implemented as any available media that can be accessed by a general purpose or special purpose computer or processor, or any programmable logic device. Suitable processor-readable media may include storage or memory media such as magnetic or optical media. For example, storage or memory media may include conventional hard disks, Compact Disk-Read Only Memory (CD-ROM), volatile or non-volatile media such as Random Access Memory (RAM) (including, but not limited to, Synchronous Dynamic Random Access Memory (SDRAM), Double Data Rate (DDR) RAM, RAMBUS Dynamic RAM (RDRAM), Static RAM (SRAM), etc.), Read Only Memory (ROM), Electrically Erasable Programmable ROM (EEPROM), and flash memory, etc. Suitable processor-readable media may also include transmission media such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a network and/or a wireless link.

Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement, which is calculated to achieve the same purpose, may be substituted for the specific embodiments shown. Therefore, it is manifestly intended that this invention be limited only by the claims and the equivalents thereof.

Example Embodiments

Example 1 includes a distributed base station radio system comprising: a first channelized to broadband conversion unit configured to receive first downlink channelized data for a first radio frequency band from a first channelized radio frequency source; wherein the first channelized to broadband conversion unit is further configured to convert the first downlink channelized data into a first downlink broadband signal; a first universal remote radio head communicatively coupled to the first channelized to broadband conversion unit; wherein the first channelized to broadband conversion unit is further configured to communicate the first downlink broadband signal to the first universal remote radio head; wherein the first universal remote radio head is configured to receive the first downlink broadband signal; wherein the first universal remote radio head is further configured to frequency convert the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band; wherein the first universal remote radio head is further configured to transmit the first downlink radio frequency signals in the first radio frequency band to a first subscriber unit.

23

Example 2 includes the distributed base station radio system of Example 1, wherein the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and wherein the first downlink channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

Example 3 includes the distributed base station radio system of any of Examples 1-2, wherein the first universal remote radio head is further communicatively coupled to a second channelized to broadband conversion unit configured to receive second downlink channelized data for a second radio frequency band from a second channelized radio frequency source; wherein the second channelized to broadband conversion unit is further configured to convert the second downlink channelized data for the second radio frequency band into a second downlink broadband signal; and wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink broadband signal to the first universal remote radio head.

Example 4 includes the distributed base station radio system of Example 3, further comprising: a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to broadband conversion unit and the first universal remote radio head, the switch configured to receive the first downlink broadband signal from the first channelized to broadband conversion unit and the second downlink broadband signal from the second channelized to broadband conversion unit and to aggregate the first downlink broadband signal with the second downlink broadband signal into an aggregate downlink broadband signal; the switch further configured to transmit the aggregate downlink broadband signal to the first universal remote radio head; the first universal remote radio head further configured to receive the aggregate downlink broadband signal and to frequency convert the aggregate downlink broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band; and the first universal remote radio head further configured to transmit the radio frequency signals in both the first radio frequency band and the second radio frequency band to at least one subscriber unit.

Example 5 includes the distributed base station radio system of Example 4, wherein the switch is configured to aggregate the first downlink broadband signal with the second downlink broadband signal through at least one of summing, multiplexing, and combining.

Example 6 includes the distributed base station radio system of any of Examples 4-5, wherein the switch is further configured to transmit the aggregate downlink broadband signal to a second universal remote radio head; wherein the second universal remote radio is configured to receive the aggregate downlink broadband signal and to frequency convert the aggregate downlink broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band; and wherein the second universal remote radio head is further configured to transmit the radio frequency signals in the first radio frequency band and the second radio frequency band to at least one subscriber unit.

Example 7 includes the distributed base station radio system of any of Examples 3-6, further comprising: a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to

24

broadband conversion unit and the first universal remote radio head, the switch configured to receive the first downlink broadband signal from the first channelized to broadband conversion unit and the second downlink broadband signal from the second channelized to broadband conversion unit and to aggregate the first downlink broadband signal with the second downlink broadband signal into an aggregate downlink broadband signal; the switch further configured to transmit the aggregate downlink broadband signal to the first universal remote radio head; the first universal remote radio head further configured to receive the aggregate downlink broadband signal, to extract the first downlink broadband signal from the aggregate downlink broadband signal, and to frequency convert the first downlink broadband signal into radio frequency signals in the first radio frequency band; the first universal remote radio head further configured to transmit the first radio frequency signals in the first radio frequency band to at least one subscriber unit.

Example 8 includes the distributed base station radio system of Example 7, wherein the first universal remote radio head is configured to extract the first downlink broadband signal from the aggregate downlink broadband signal through at least one of de-multiplexing and splitting apart.

Example 9 includes the distributed base station radio system of any of Examples 1-8, wherein the first universal remote radio head is further communicatively coupled to a second channelized to broadband conversion unit configured to receive second downlink channelized data for a second radio frequency band from a second channelized radio frequency source; wherein the second channelized to broadband conversion unit is further configured to convert the second downlink channelized data into a second downlink broadband signal; wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink broadband signal to the first universal remote radio head; wherein the first universal remote radio head is further configured to receive the second downlink broadband signal; wherein the first universal remote radio head is further configured to frequency convert the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band; and wherein the first universal remote radio head is further configured to transmit the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit.

Example 10 includes the distributed base station radio system of Example 9, wherein the first universal remote radio head includes a first radio frequency converter configured to frequency convert the first downlink broadband signal into the first downlink radio frequency signals in the first radio frequency band; wherein the first universal remote radio head includes a second radio frequency converter configured to frequency convert the second downlink broadband signal into the second downlink radio frequency signals; wherein the first universal remote radio head includes a first power amplifier, radio frequency transceiver, and antenna set configured to transmit the first radio frequency band; and wherein the first universal remote radio head includes a second power amplifier, radio frequency transceiver, and antenna set configured to transmit the second radio frequency band.

Example 11 includes the distributed base station radio system of Example 10, wherein the first downlink radio frequency signals and the second downlink radio frequency signals are MIMO signals transmitted to a single subscriber unit.

Example 12 includes the distributed base station radio system of any of Examples 7-11, wherein the first universal remote radio head includes a first radio frequency converter

25

configured to frequency convert the first downlink broadband signal into the first downlink radio frequency signals in the first radio frequency band; wherein the first universal remote radio head includes a second radio frequency converter configured to frequency convert the second downlink broadband signal into the second downlink radio frequency signals in the second radio frequency band; and wherein the first universal remote radio head includes a single power amplifier, radio frequency transceiver, and antenna set configured to transmit both the first radio frequency band and the second radio frequency band.

Example 13 includes the distributed base station radio system of any of Examples 7-12, wherein the first universal remote radio head includes a single radio frequency converter configured to frequency convert both the first downlink broadband signal into the first downlink radio frequency signals in the first radio frequency band and the second downlink broadband signal into the second downlink radio frequency signals in the second radio frequency band; and wherein the first universal remote radio head includes a single power amplifier, radio frequency transceiver, and antenna set configured to transmit both the first radio frequency band and the second radio frequency band.

Example 14 includes the distributed base station radio system of any of Examples 1-13, further comprising: a second channelized to broadband conversion unit configured to receive second downlink channelized data for a second radio frequency band from a second channelized radio frequency source; wherein the second channelized to broadband conversion unit is further configured to convert the second downlink channelized data into a second downlink broadband signal; a second universal remote radio head communicatively coupled to the second channelized to broadband conversion unit; a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to broadband conversion unit and the first universal remote radio head and the second universal remote radio head; wherein the first channelized to broadband conversion unit is further configured to communicate the first downlink broadband signal to the switch; wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink broadband signal to the switch; wherein the switch is configured to communicate the first downlink broadband signal to the first universal remote radio head; wherein the switch is configured to communicate the second downlink broadband signal to the second universal remote radio head; wherein the second universal remote radio head is configured to receive the second downlink broadband signal; wherein the second universal remote radio head is further configured to frequency convert the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band; and wherein the second universal remote radio head is further configured to transmit the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit.

Example 15 includes the distributed base station radio system of any of Examples 1-14, wherein the first channelized radio frequency source is a base band unit of a wireless access base station.

Example 16 includes the distributed base station radio system of any of Examples 1-15, further comprising: wherein the first universal remote radio head is further configured to receive uplink radio frequency signals in the first radio frequency band from the first subscriber unit; wherein the first universal remote radio head is further configured to frequency convert the uplink radio frequency signals in the first radio

26

frequency band into an uplink broadband signal; wherein the first universal remote radio head is further configured to communicate the uplink broadband signal to the first channelized to broadband conversion unit; wherein the first channelized to broadband conversion unit is further configured to receive the uplink broadband signal; wherein the first channelized to broadband conversion unit is further configured to convert the uplink broadband signal into uplink channelized data for the first radio frequency band; and wherein the first channelized to broadband conversion unit is further configured to communicate the uplink channelized data for the first radio frequency band to the first channelized radio frequency source.

Example 17 includes the distributed base station radio system of Example 16, wherein downlink and uplink signals within the first radio frequency band are in distinct spectrum.

Example 18 includes the distributed base station radio system of any of Examples 16-17, wherein downlink and uplink signals within the first radio frequency band overlap in spectrum.

Example 19 includes the distributed base station radio system of any of Examples 16-18, wherein the downlink and uplink signals within the first radio frequency band are separated in time using a Time Division Duplexing (TDD) scheme.

Example 20 includes a method comprising: receiving first downlink channelized data for a first radio frequency band from a first channelized radio frequency source at a first channelized to broadband conversion unit; converting the first downlink channelized data into a first downlink broadband signal at the first channelized to broadband conversion unit; communicating the first downlink broadband signal to a first universal remote radio head from the first channelized to broadband conversion unit; frequency converting the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band at the first universal remote radio head; and transmitting the first downlink radio frequency signals in the first radio frequency band to a first subscriber unit at the first universal remote radio head.

Example 21 includes the method of Example 20, wherein the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and wherein the first downlink channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

Example 22 includes the method of any of Examples 20-21, further comprising: receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit; convert the second downlink channelized data for the second radio frequency band into a second downlink broadband signal at the second channelized to broadband conversion unit; communicating the second downlink broadband signal from the second channelized to broadband conversion unit to the first universal remote radio head; frequency converting the second downlink broadband signal into radio frequency signals in the second radio frequency band; and transmitting the radio frequency signals in the second radio frequency band to at least one subscriber unit at the first universal remote radio head.

Example 23 includes the method of Example 22, further comprising: receiving the first downlink broadband signal from the first channelized to broadband conversion unit at a

switch; receiving the second downlink broadband signal from the second channelized to broadband conversion unit at the switch; aggregating the first downlink broadband signal with the second downlink broadband signal into an aggregate downlink broadband signal at the switch; and communicating the aggregate downlink broadband signal from the switch to the first universal remote radio head.

Example 24 includes the method of Example 23, wherein aggregating the first downlink broadband signal with the second downlink broadband signal into an aggregate downlink broadband signal at the switch includes at least one of summing, multiplexing, and combining the first downlink broadband signal with the second downlink broadband signal.

Example 25 includes the method of any of Examples 23-24, further comprising: communicating the aggregate downlink broadband signal from the switch to a second universal remote radio head; converting the aggregate downlink broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band at the second universal remote radio head; and transmitting the radio frequency signals in both the first radio frequency band and the second radio frequency band at the second universal remote radio head.

Example 26 includes the method of any of Examples 23-25, further comprising: communicating the aggregate downlink broadband signal from the switch to a second universal remote radio head; extracting the second downlink broadband signals from the aggregate downlink broadband signal; converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band at the second universal remote radio head; and transmitting the second downlink radio frequency signals in the second radio frequency band at the second universal remote radio head.

Example 27 includes the method of Example 26, wherein extracting the second downlink broadband signals from the aggregate downlink broadband signal includes at least one of de-multiplexing and splitting apart.

Example 28 includes the method of any of Examples 22-27, further comprising: receiving the first downlink broadband signal from the first channelized to broadband conversion unit at a switch; receiving the second downlink broadband signal from the second channelized to broadband conversion unit at the switch; aggregating the first downlink broadband signal with the second downlink broadband signals into an aggregate downlink broadband signal at the switch; communicating the aggregate downlink broadband signal from the switch to the first universal remote radio head; frequency converting the aggregate downlink broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band; and transmitting the radio frequency signals in both the first radio frequency band and the second radio frequency band to at least one subscriber unit at the first universal remote radio head.

Example 29 includes the method of any of Examples 20-28, further comprising: receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit; converting the second downlink channelized data into a second downlink broadband signal; communicating the second downlink broadband signal to the first universal remote radio head from the second channelized to broadband conversion unit; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band at the first universal remote radio head; and transmitting the

second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit.

Example 30 includes the method of Example 29, wherein frequency converting the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head; wherein frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head; wherein transmitting the first downlink radio frequency signals in the first radio frequency band to a first subscriber unit at the first universal remote radio head occurs at a first power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head; and wherein transmitting the second downlink radio frequency signals in the second radio frequency band to a second subscriber unit at the first universal remote radio head occurs at a second power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head.

Example 31 includes the method of Example 30, wherein the first downlink radio frequency signals and the second downlink radio frequency signals are MIMO signals transmitted to a single subscriber unit.

Example 32 includes the method of any of Examples 29-31, wherein frequency converting the first downlink broadband signal into first downlink radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head; wherein frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head; and wherein transmitting both the first downlink radio frequency signals in the first radio frequency band and the second downlink radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

Example 33 includes the method of any of Examples 29-32, wherein frequency converting both the first downlink broadband signal into the first downlink radio frequency signals in the first radio frequency band and the second downlink broadband signals into the second downlink radio frequency signals in the second radio frequency band occurs at a single radio frequency converter; and wherein transmitting both the first downlink radio frequency signals in the first radio frequency band and the second downlink radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

Example 34 includes the method of any of Examples 20-33, further comprising: communicating the first downlink broadband signal from the first channelized to broadband conversion unit to a switch; receiving second downlink channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit; converting the second downlink channelized data into a second downlink broadband signal at the second channelized to broadband conversion unit; communicating the second downlink broadband signal from the second channelized to broadband conversion unit to the switch; communicating the first downlink broadband signal from the switch to the first universal remote radio head; communicating the second downlink broadband signal from the switch to the second universal remote radio head; frequency converting the second downlink broadband signal into second downlink radio frequency signals in the second radio frequency band at the second universal remote radio head; and

29

transmitting the second downlink radio frequency signals in the second radio frequency band to at least one subscriber unit at the second universal remote radio head.

Example 35 includes the method of any of Examples 20-34, further comprising: receiving uplink radio frequency signals in the first radio frequency band from the first subscriber unit at the first universal remote radio head; frequency converting the uplink radio frequency signals in the first radio frequency band into an uplink broadband signal at the first universal remote radio head; communicating the uplink broadband signal to the first channelized to broadband conversion unit from the first universal remote radio head; converting the uplink broadband signal into uplink channelized data for the first radio frequency band at the first channelized to broadband conversion unit; and communicating the uplink channelized data for the first radio frequency band to the first channelized radio frequency source at the first channelized to broadband conversion unit.

Example 36 includes the method of Example 35, wherein downlink and uplink signals within the first radio frequency band are in distinct spectrum.

Example 37 includes the method of any of Examples 35-36, wherein downlink and uplink signals within the first radio frequency band overlap in spectrum.

Example 38 includes the method of any of Examples 35-37, wherein the downlink and uplink signals within the first radio frequency band are separated in time using a Time Division Duplexing (TDD) scheme.

Example 39 includes a universal remote radio head comprising: an interface configured to receive a downlink broadband signal including digitized data for a radio frequency band from a remote channelized to broadband conversion module; a frequency converter configured to frequency convert the downlink broadband signal into downlink radio frequency signals in the radio frequency band; a radio frequency transceiver and antenna pair configured to transmit the downlink radio frequency signals in the radio frequency band to a first subscriber unit; the radio frequency transceiver and antenna pair further configured to receive uplink radio frequency signals in the radio frequency band from the first subscriber unit; the frequency converter further configured to frequency convert the uplink radio frequency signals in the radio frequency band into an uplink broadband signal; and wherein the interface is configured to communicate the uplink broadband signal including digitized data for the radio frequency band to the remote channelized to broadband conversion module.

Example 40 includes a method comprising: receiving a downlink broadband signal including digitized data from a radio frequency band communicated from a remote channelized to broadband conversion module at a universal remote radio head; frequency converting the downlink broadband signal into downlink radio frequency signals in the radio frequency band at the universal remote radio head; transmitting the downlink radio frequency signals in the radio frequency band to a first subscriber unit; receiving uplink radio frequency signals in the radio frequency band from the first subscriber unit; frequency converting the uplink radio frequency signals in the radio frequency band into an uplink broadband signal; and communicating the uplink broadband signal to the remote channelized to broadband conversion module at the universal remote radio head.

Example 41 includes a channelized to broadband conversion unit comprising: a first interface configured to receive first downlink channelized data for a radio frequency band from a channelized radio frequency source coupled to the channelized to broadband conversion unit; a converter con-

30

figured to convert the first downlink channelized data into a downlink broadband signal; a second interface configured to communicate the downlink broadband signal to a universal remote radio head; wherein the second interface is further configured to receive an uplink broadband signal from the universal remote radio head; wherein the converter is further configured to convert the uplink broadband signal from the universal remote radio head into uplink channelized data for the radio frequency band; and wherein the first interface is further configured to communicate uplink channelized data for the radio frequency band to the channelized radio frequency source coupled to the channelized to broadband conversion unit.

Example 42 includes the channelized to broadband conversion unit of Example 41, wherein the channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and wherein the first downlink channelized data and the uplink channelized data are formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

Example 43 includes a method comprising: receiving downlink channelized data for a radio frequency band from an channelized radio frequency source at a channelized to broadband conversion unit; converting the downlink channelized data into a downlink broadband signal at the channelized to broadband conversion unit; communicating the downlink broadband signal to a universal remote radio head; receiving an uplink broadband signal from the universal remote radio head; converting the uplink broadband signal into uplink channelized data for the radio frequency band at the channelized to broadband conversion unit; and communicating the uplink channelized data for the radio frequency band to the channelized radio frequency source coupled to the channelized to broadband conversion unit.

Example 44 includes the method of Example 43, wherein the channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and wherein the downlink channelized data and the uplink channelized data are formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

What is claimed is:

1. A distributed base station radio system comprising:
 - a first channelized to broadband conversion unit configured to receive first downlink digital channelized data for a first radio frequency band from a first channelized radio frequency source, wherein the first downlink digital channelized data is specific to a first channel;
 - wherein the first channelized to broadband conversion unit is further configured to convert the first downlink digital channelized data into a first downlink digital broadband signal having a single center frequency, wherein the first downlink digital broadband signal is configured to represent a portion of radio frequency spectrum having a plurality of channels, the plurality of channels including the first channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the first downlink digital broadband signal that

31

reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

a first universal remote radio head communicatively coupled to the first channelized to broadband conversion unit;

wherein the first channelized to broadband conversion unit is further configured to communicate the first downlink digital broadband signal to the first universal remote radio head;

wherein the first universal remote radio head is configured to receive the first downlink digital broadband signal;

wherein the first universal remote radio head is further configured to convert the first downlink digital broadband signal into first downlink analog radio frequency signals in the first radio frequency band through at least one of frequency conversion and digital to analog conversion;

wherein the first universal remote radio head is further configured to transmit the first downlink analog radio frequency signals in the first radio frequency band to a first subscriber unit.

2. The distributed base station radio system of claim 1, wherein the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and

wherein the first downlink digital channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

3. The distributed base station radio system of claim 1, further comprising:

wherein the first universal remote radio head is further communicatively coupled to a second channelized to broadband conversion unit configured to receive second downlink digital channelized data for a second radio frequency band from a second channelized radio frequency source, wherein the second downlink digital channelized data is specific to a second channel;

wherein the second channelized to broadband conversion unit is further configured to convert the second downlink digital channelized data for the second radio frequency band into a second downlink digital broadband signal having the single center frequency, wherein the second downlink digital broadband signal is configured to represent the portion of radio frequency having the plurality of channels, the plurality of channels including the second channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the second downlink digital broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink digital broadband signal to the first universal remote radio head;

wherein the first universal remote radio head is configured to receive the second downlink digital broadband signal;

wherein the first universal remote radio head is configured to convert the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

32

wherein the first universal remote radio head is further configured to transmit the second downlink analog radio frequency signals in the second radio frequency band to a second subscriber unit.

4. The distributed base station radio system of claim 3, further comprising:

a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to broadband conversion unit and the first universal remote radio head, the switch configured to receive the first downlink digital broadband signal from the first channelized to broadband conversion unit and the second downlink digital broadband signal from the second channelized to broadband conversion unit and to sum the first downlink digital broadband signal with the second downlink digital broadband signal into an aggregate downlink digital broadband signal;

the switch further configured to transmit the aggregate downlink digital broadband signal to the first universal remote radio head;

the first universal remote radio head further configured to receive the aggregate downlink digital broadband signal and to convert the aggregate downlink digital broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

the first universal remote radio head further configured to transmit the radio frequency signals in both the first radio frequency band and the second radio frequency band to at least one subscriber unit.

5. The distributed base station radio system of claim 4, wherein the switch is further configured to transmit the aggregate downlink digital broadband signal to a second universal remote radio head;

wherein the second universal remote radio is configured to receive the aggregate downlink digital broadband signal and to convert the aggregate downlink digital broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

wherein the second universal remote radio head is further configured to transmit the radio frequency signals in the first radio frequency band and the second radio frequency band to at least one subscriber unit.

6. The distributed base station radio system of claim 3, further comprising:

a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to broadband conversion unit and the first universal remote radio head, the switch configured to receive the first downlink digital broadband signal from the first channelized to broadband conversion unit and the second downlink digital broadband signal from the second channelized to broadband conversion unit and to aggregate the first downlink digital broadband signal with the second downlink digital broadband signal into an aggregate downlink digital broadband signal; the switch further configured to transmit the aggregate downlink digital broadband signal to the first universal remote radio head;

the first universal remote radio head further configured to receive the aggregate downlink digital broadband signal, to extract the first downlink digital broadband signal from the aggregate downlink digital broadband signal,

33

and to frequency convert the first downlink digital broadband signal into radio frequency signals in the first radio frequency band;

the first universal remote radio head further configured to transmit the first radio frequency signals in the first radio frequency band to at least one subscriber unit.

7. The distributed base station radio system of claim 6, wherein the first universal remote radio head is configured to extract the first downlink digital broadband signal from the aggregate downlink digital broadband signal through at least one of de-multiplexing and splitting apart.

8. The distributed base station radio system of claim 1, wherein the first universal remote radio head is further communicatively coupled to a second channelized to broadband conversion unit configured to receive second downlink digital channelized data for a second radio frequency band from a second channelized radio frequency source, wherein the second downlink digital channelized data is specific to a second channel;

wherein the second channelized to broadband conversion unit is further configured to convert the second downlink digital channelized data into a second downlink digital broadband signal having the single center frequency, wherein the second downlink digital broadband signal is configured to represent the portion of radio frequency having the plurality of channels, the plurality of channels including the second channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the second downlink digital broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink digital broadband signal to the first universal remote radio head;

wherein the first universal remote radio head is further configured to receive the second downlink digital broadband signal;

wherein the first universal remote radio head is further configured to frequency convert and digital to analog convert the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band; and

wherein the first universal remote radio head is further configured to transmit the second downlink analog radio frequency signals in the second radio frequency band to at least one subscriber unit.

9. The distributed base station radio system of claim 8, wherein the first universal remote radio head includes a first radio frequency converter configured to frequency convert the first downlink digital broadband signal into the first downlink analog radio frequency signals in the first radio frequency band;

wherein the first universal remote radio head includes a second radio frequency converter configured to frequency convert the second downlink digital broadband signal into the second downlink analog radio frequency signals;

wherein the first universal remote radio head includes a first power amplifier, radio frequency transceiver, and antenna set configured to transmit the first radio frequency band; and

wherein the first universal remote radio head includes a second power amplifier, radio frequency transceiver, and antenna set configured to transmit the second radio frequency band.

34

10. The distributed base station radio system of claim 9, wherein the first downlink analog radio frequency signals and the second downlink analog radio frequency signals are MIMO signals transmitted to a single subscriber unit.

11. The distributed base station radio system of claim 6, wherein the first universal remote radio head includes a first radio frequency converter configured to frequency convert the first downlink digital broadband signal into the first downlink analog radio frequency signals in the first radio frequency band;

wherein the first universal remote radio head includes a second radio frequency converter configured to frequency convert the second downlink digital broadband signal into the second downlink analog radio frequency signals in the second radio frequency band; and

wherein the first universal remote radio head includes a single power amplifier, radio frequency transceiver, and antenna set configured to transmit both the first radio frequency band and the second radio frequency band.

12. The distributed base station radio system of claim 6, wherein the first universal remote radio head includes a single radio frequency converter configured to frequency convert both the first downlink digital broadband signal into the first downlink analog radio frequency signals in the first radio frequency band and the second downlink digital broadband signal into the second downlink analog radio frequency signals in the second radio frequency band; and

wherein the first universal remote radio head includes a single power amplifier, radio frequency transceiver, and antenna set configured to transmit both the first radio frequency band and the second radio frequency band.

13. The distributed base station radio system of claim 1, further comprising:

a second channelized to broadband conversion unit configured to receive second downlink digital channelized data for a second radio frequency band from a second channelized radio frequency source, wherein the second downlink digital channelized data is specific to a second channel;

wherein the second channelized to broadband conversion unit is further configured to convert the second downlink digital channelized data into a second downlink digital broadband signal having the single center frequency, wherein the second downlink digital broadband signal is configured to represent the portion of radio frequency having the plurality of channels, the plurality of channels including the second channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the second downlink broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

a second universal remote radio head communicatively coupled to the second channelized to broadband conversion unit;

a switch communicatively coupled between both the first channelized to broadband conversion unit and the second channelized to broadband conversion unit and the first universal remote radio head and the second universal remote radio head;

wherein the first channelized to broadband conversion unit is further configured to communicate the first downlink digital broadband signal to the switch;

wherein the second channelized to broadband conversion unit is further configured to communicate the second downlink digital broadband signal to the switch;

35

wherein the switch is configured to communicate the first downlink digital broadband signal to the first universal remote radio head;

wherein the switch is configured to communicate the second downlink digital broadband signal to the second universal remote radio head;

wherein the second universal remote radio head is configured to receive the second downlink digital broadband signal;

wherein the second universal remote radio head is further configured to convert the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

wherein the second universal remote radio head is further configured to transmit the second downlink analog radio frequency signals in the second radio frequency band to at least one subscriber unit.

14. The distributed base station radio system of claim **1**, wherein the first channelized radio frequency source is a base band unit of a wireless access base station.

15. The distributed base station radio system of claim **1**, further comprising:

wherein the first universal remote radio head is further configured to receive uplink analog radio frequency signals in the first radio frequency band from the first subscriber unit;

wherein the first universal remote radio head is further configured to convert the uplink analog radio frequency signals in the first radio frequency band into an uplink digital broadband signal through at least one of frequency conversion and analog to digital conversion;

wherein the first universal remote radio head is further configured to communicate the uplink digital broadband signal to the first channelized to broadband conversion unit;

wherein the first channelized to broadband conversion unit is further configured to receive the uplink digital broadband signal;

wherein the first channelized to broadband conversion unit is further configured to convert the uplink digital broadband signal into uplink digital channelized data for the first radio frequency band; and

wherein the first channelized to broadband conversion unit is further configured to communicate the uplink digital channelized data for the first radio frequency band to the first channelized radio frequency source.

16. The distributed base station radio system of claim **15**, wherein downlink and uplink signals within the first radio frequency band are in distinct spectrum.

17. The distributed base station radio system of claim **15**, wherein downlink and uplink signals within the first radio frequency band overlap in spectrum.

18. The distributed base station radio system of claim **15**, wherein downlink and uplink signals within the first radio frequency band are separated in time using a Time Division Duplexing (TDD) scheme.

19. A method comprising:

receiving first downlink digital channelized data for a first radio frequency band from a first channelized radio frequency source at a first channelized to broadband conversion unit, wherein the first downlink digital channelized data is specific to a first channel;

converting the first downlink digital channelized data into a first downlink digital broadband signal at the first channelized to broadband conversion unit, wherein the

36

first downlink digital broadband signal has a single center frequency, wherein the first downlink digital broadband signal is configured to represent a portion of radio frequency spectrum having a plurality of channels, the plurality of channels including the first channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the first downlink digital broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

communicating the first downlink digital broadband signal to a first universal remote radio head from the first channelized to broadband conversion unit;

converting the first downlink digital broadband signal into first downlink analog radio frequency signals in the first radio frequency band at the first universal remote radio head through at least one of frequency conversion and digital to analog conversion; and

transmitting the first downlink analog radio frequency signals in the first radio frequency band to a first subscriber unit at the first universal remote radio head.

20. The method of claim **19**, wherein the first channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and

wherein the first downlink digital channelized data is formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

21. The method of claim **19**, further comprising:

receiving second downlink digital channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit, wherein the second downlink digital channelized data is specific to a second channel;

converting the second downlink digital channelized data for the second radio frequency band into a second downlink digital broadband signal at the second channelized to broadband conversion unit, wherein the second downlink digital broadband signal has the single center frequency, wherein the second downlink digital broadband signal is configured to represent the portion of radio frequency having the plurality of channels, the plurality of channels including the second channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the second downlink digital broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

communicating the second downlink digital broadband signal from the second channelized to broadband conversion unit to the first universal remote radio head;

converting the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

transmitting the second downlink analog radio frequency signals in the second radio frequency band to at least one subscriber unit at the first universal remote radio head.

22. The method of claim **21**, further comprising:

receiving the first downlink digital broadband signal from the first channelized to broadband conversion unit at a switch;

37

receiving the second downlink digital broadband signal from the second channelized to broadband conversion unit at the switch;

summing the first downlink digital broadband signal with the second downlink digital broadband signal into an aggregate downlink digital broadband signal at the switch; and

communicating the aggregate downlink digital broadband signal from the switch to the first universal remote radio head.

23. The method of claim **22**, further comprising:

communicating the aggregate downlink digital broadband signal from the switch to a second universal remote radio head;

converting the aggregate downlink digital broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band at the second universal remote radio head through at least one of frequency conversion and digital to analog conversion; and

transmitting the radio frequency signals in both the first radio frequency band and the second radio frequency band at the second universal remote radio head.

24. The method of claim **22**, further comprising:

communicating the aggregate downlink digital broadband signal from the switch to a second universal remote radio head;

extracting the second downlink digital broadband signals from the aggregate downlink digital broadband signal;

converting the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band at the second universal remote radio head; and

transmitting the second downlink analog radio frequency signals in the second radio frequency band at the second universal remote radio head.

25. The method of claim **21**, further comprising:

receiving the first downlink digital broadband signal from the first channelized to broadband conversion unit at a switch;

receiving the second downlink digital broadband signal from the second channelized to broadband conversion unit at the switch;

summing the first downlink digital broadband signal with the second downlink digital broadband signals into an aggregate downlink digital broadband signal at the switch;

communicating the aggregate downlink digital broadband signal from the switch to the first universal remote radio head;

converting the aggregate downlink digital broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band through at least one of frequency conversion and digital to analog conversion; and

transmitting the radio frequency signals in both the first radio frequency band and the second radio frequency band to at least one subscriber unit at the first universal remote radio head.

26. The method of claim **19**, further comprising:

receiving second downlink digital channelized data for a second radio frequency band from a second channelized radio frequency source at a second channelized to broadband conversion unit;

converting the second downlink digital channelized data into a second downlink digital broadband signal;

38

communicating the second downlink digital broadband signal to the first universal remote radio head from the second channelized to broadband conversion unit;

converting the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band at the first universal remote radio head through at least one of frequency conversion and digital to analog conversion; and

transmitting the second downlink analog radio frequency signals in the second radio frequency band to at least one subscriber unit.

27. The method of claim **26**, wherein frequency converting the first downlink digital broadband signal into first downlink analog radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head;

wherein converting the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head;

wherein transmitting the first downlink analog radio frequency signals in the first radio frequency band to a first subscriber unit at the first universal remote radio head occurs at a first power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head; and

wherein transmitting the second downlink analog radio frequency signals in the second radio frequency band to a second subscriber unit at the first universal remote radio head occurs at a second power amplifier, radio frequency transceiver, and antenna set of the first universal remote radio head.

28. The method of claim **27**, wherein the first downlink analog radio frequency signals and the second downlink analog radio frequency signals are MIMO signals transmitted to a single subscriber unit.

29. The method of claim **26**, wherein frequency converting the first downlink digital broadband signal into first downlink analog radio frequency signals in the first radio frequency band occurs at a first frequency converter of the first universal remote radio head;

wherein converting the second downlink digital broadband signal into second downlink analog radio frequency signals in the second radio frequency band occurs at a second frequency converter of the first universal remote radio head; and

wherein transmitting both the first downlink analog radio frequency signals in the first radio frequency band and the second downlink analog radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

30. The method of claim **26**, wherein converting both the first downlink digital broadband signal into the first downlink analog radio frequency signals in the first radio frequency band and the second downlink digital broadband signals into the second downlink analog radio frequency signals in the second radio frequency band occurs at a single radio frequency converter; and

wherein transmitting both the first downlink analog radio frequency signals in the first radio frequency band and the second downlink analog radio frequency signals in the second radio frequency band occurs at a single power amplifier, radio frequency transceiver, and antenna set.

39

31. The method of claim 19, further comprising:
communicating the first downlink digital broadband signal
from the first channelized to broadband conversion unit
to a switch;
receiving second downlink digital channelized data for a
second radio frequency band from a second channelized
radio frequency source at a second channelized to broad-
band conversion unit, wherein the second downlink digi-
tal channelized data is specific to a second channel;
converting the second downlink digital channelized data
into a second downlink digital broadband signal at the
second channelized to broadband conversion unit,
wherein the second downlink digital broadband signal
has the single center frequency, wherein the second
downlink digital broadband signal is configured to rep-
resent the portion of radio frequency having the plurality
of channels, the plurality of channels including the sec-
ond channel, wherein each of the plurality of channels is
configured to be in non-overlapping locations within the
second downlink digital broadband signal that reflects
the location of each channel within the portion of radio
frequency spectrum relative to the plurality of channels;
communicating the second downlink digital broadband
signal from the second channelized to broadband con-
version unit to the switch;
communicating the first downlink digital broadband signal
from the switch to the first universal remote radio head;
communicating the second downlink digital broadband
signal from the switch to the second universal remote
radio head;
converting the second downlink digital broadband signal
into second downlink analog radio frequency signals in
the second radio frequency band at the second universal
remote radio head through at least one of frequency
conversion and digital to analog conversion; and
transmitting the second downlink analog radio frequency
signals in the second radio frequency band to at least one
subscriber unit at the second universal remote radio
head.

32. The method of claim 19, further comprising:
receiving uplink analog radio frequency signals in the first
radio frequency band from the first subscriber unit at the
first universal remote radio head;
converting the uplink analog radio frequency signals in the
first radio frequency band into an uplink digital broad-
band signal at the first universal remote radio head
through at least one of frequency conversion and analog
to digital conversion;
communicating the uplink digital broadband signal to the
first channelized to broadband conversion unit from the
first universal remote radio head;
converting the uplink digital broadband signal into uplink
digital channelized data for the first radio frequency
band at the first channelized to broadband conversion
unit; and
communicating the uplink digital channelized data for the
first radio frequency band to the first channelized radio
frequency source at the first channelized to broadband
conversion unit.

33. The method of claim 32, wherein downlink and uplink
signals within the first radio frequency band are in distinct
spectrum.

34. The method of claim 32, wherein downlink and uplink
signals within the first radio frequency band overlap in spec-
trum.

40

35. The method of claim 32, wherein downlink and uplink
signals within the first radio frequency band are separated in
time using a Time Division Duplexing (TDD) scheme.

36. A universal remote radio head comprising:
an interface configured to receive a downlink digital broad-
band signal including digitized data for a radio fre-
quency band from a remote channelized to broadband
conversion module, wherein the downlink digital broad-
band signal includes a single center frequency, wherein
the downlink digital broadband signal is configured to
represent a portion of radio spectrum having a plurality
of channels, wherein each of the plurality of channels is
configured to be in non-overlapping locations within the
first downlink digital broadband signal that reflect the
location of each channel within the portion of radio
frequency spectrum relative to the plurality of channels;
a converter configured to convert the downlink digital
broadband signal into downlink analog radio frequency
signals in the radio frequency band through at least one
of frequency conversion and digital to analog conver-
sion;
a radio frequency transceiver and antenna pair configured
to transmit the downlink analog radio frequency signals
in the radio frequency band to a first subscriber unit;
the radio frequency transceiver and antenna pair further
configured to receive uplink analog radio frequency sig-
nals in the radio frequency band from the first subscriber
unit;
the converter further configured to convert the uplink ana-
log radio frequency signals in the radio frequency band
into an uplink digital broadband signal through at least
one of frequency conversion and analog to digital con-
version; and
wherein the interface is configured to communicate the
uplink digital broadband signal including digitized data
for the radio frequency band to the remote channelized
to broadband conversion module.

37. A method comprising:
receiving a downlink digital broadband signal including
digitized data from a radio frequency band communi-
cated from a remote channelized to broadband conver-
sion module at a universal remote radio head, wherein
the downlink digital broadband signal includes a single
center frequency, wherein the downlink digital broad-
band signal is configured to represent a portion of radio
spectrum having a plurality of channels, wherein each of
the plurality of channels is configured to be in non-
overlapping locations within the first downlink digital
broadband signal that reflects the location of each chan-
nel within the portions of radio frequency spectrum rela-
tive to the plurality of channels;
converting the downlink digital broadband signal into
downlink analog radio frequency signals in the radio
frequency band at the universal remote radio head
through at least one of frequency conversion and digital
to analog conversion;
transmitting the downlink analog radio frequency signals
in the radio frequency band to a first subscriber unit;
receiving uplink analog radio frequency signals in the radio
frequency band from the first subscriber unit;
converting the uplink analog radio frequency signals in the
radio frequency band into an uplink digital broadband
signal through at least one of frequency conversion and
analog to digital conversion; and
communicating the uplink digital broadband signal to the
remote channelized to broadband conversion module at
the universal remote radio head.

41

38. A channelized to broadband conversion unit comprising:

a first interface configured to receive first downlink digital channelized data for a radio frequency band from a channelized radio frequency source coupled to the channelized to broadband conversion unit, wherein the first downlink digital channelized data is specific to a first channel;

a converter configured to convert the first downlink digital channelized data into a downlink digital broadband signal having a single center frequency, wherein the first downlink digital broadband signal is configured to represent a portion of radio frequency spectrum having a plurality of channels, the plurality of channels including the first channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the first downlink digital broadband signal that reflect the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

a second interface configured to communicate the downlink digital broadband signal to a universal remote radio head;

wherein the second interface is further configured to receive an uplink digital broadband signal from the universal remote radio head;

wherein the converter is further configured to convert the uplink digital broadband signal from the universal remote radio head into uplink digital channelized data for the radio frequency band; and

wherein the first interface is further configured to communicate uplink digital channelized data for the radio frequency band to the channelized radio frequency source coupled to the channelized to broadband conversion unit.

39. The channelized to broadband conversion unit of claim 38, wherein the channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and

wherein the first downlink digital channelized data and the uplink digital channelized data are formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

40. A method comprising:

receiving downlink digital channelized data for a radio frequency band from an channelized radio frequency source at a channelized to broadband conversion unit, wherein the first downlink digital channelized data is specific to a first channel;

converting the downlink digital channelized data into a downlink digital broadband signal at the channelized to broadband conversion unit, wherein the downlink digital broadband signal has a single center frequency, wherein the downlink digital broadband signal is configured to represent a portion of radio frequency spectrum having a plurality of channels, the plurality of channels including the first channel, wherein each of the plurality of channels is configured to be in non-overlapping locations within the downlink digital broadband

42

signal that reflects the location of each channel within the portion of radio frequency spectrum relative to the plurality of channels;

communicating the downlink digital broadband signal to a universal remote radio head;

receiving an uplink digital broadband signal from the universal remote radio head;

converting the uplink digital broadband signal into uplink digital channelized data for the radio frequency band at the channelized to broadband conversion unit; and

communicating the uplink digital channelized data for the radio frequency band to the channelized radio frequency source coupled to the channelized to broadband conversion unit.

41. The method of claim 40, wherein the channelized radio frequency source is at least one of a Common Public Radio Interface (CPRI) base station interface, an Open Base Station Architecture Initiative (OBSAI) base station interface, and an Open Radio Interface (ORI) interface; and

wherein the downlink digital channelized data and the uplink digital channelized data are formatted according to at least one of a Common Public Radio Interface (CPRI) standard, an Open Base Station Architecture Initiative (OBSAI) standard, and an Open Radio Interface (ORI) standard.

42. The distributed base station radio system of claim 1, further comprising:

a switch communicatively coupled between the first channelized to broadband conversion unit and the first universal remote radio head, the switch configured to receive the first downlink digital broadband signal from the first channelized to broadband conversion unit and a second downlink digital broadband signal from another device and to sum the first downlink digital broadband signal with the second downlink digital broadband signal into an aggregate downlink digital broadband signal; the switch further configured to transmit the aggregate downlink digital broadband signal to the first universal remote radio head;

the first universal remote radio head further configured to receive the aggregate downlink digital broadband signal and to frequency convert the aggregate downlink digital broadband signal into radio frequency signals in both the first radio frequency band and the second radio frequency band; and

the first universal remote radio head further configured to transmit the radio frequency signals in both the first radio frequency band and the second radio frequency band to at least one subscriber unit.

43. The method of claim 19, further comprising:

receiving the first downlink digital broadband signal from the first channelized to broadband conversion unit at a switch;

receiving a second downlink digital broadband signal from a second device at the switch;

summing the first downlink digital broadband signal with the second downlink digital broadband signal into an aggregate downlink digital broadband signal at the switch; and

communicating the aggregate downlink digital broadband signal from the switch to the first universal remote radio head.

* * * * *